

1			2			3			4			5			6			7			8			9			10																							
MODEL NO: KFMCRQ-6																																																		
DESIGN DATA <table><thead><tr><th>SR.NO.</th><th>PARTICULARS</th><th>DESCRIPTION</th></tr></thead><tbody><tr><td>01</td><td>Capacity</td><td>6 Ltr. ± 5%</td></tr><tr><td>02</td><td>Temprature range</td><td>+5°C to +55°C</td></tr><tr><td>03</td><td>Service pressure</td><td>14 bar</td></tr><tr><td>04</td><td>Maximum service Pressure</td><td>16 bar</td></tr><tr><td>05</td><td>Pressure test (PT)</td><td>35 bar</td></tr><tr><td>06</td><td>Minimum Burst Pressure Test(PB)</td><td>55 bar</td></tr></tbody></table>																														SR.NO.	PARTICULARS	DESCRIPTION	01	Capacity	6 Ltr. ± 5%	02	Temprature range	+5°C to +55°C	03	Service pressure	14 bar	04	Maximum service Pressure	16 bar	05	Pressure test (PT)	35 bar	06	Minimum Burst Pressure Test(PB)	55 bar
																														SR.NO.	PARTICULARS	DESCRIPTION																		
01	Capacity	6 Ltr. ± 5%																																																
02	Temprature range	+5°C to +55°C																																																
03	Service pressure	14 bar																																																
04	Maximum service Pressure	16 bar																																																
05	Pressure test (PT)	35 bar																																																
06	Minimum Burst Pressure Test(PB)	55 bar																																																
PERFORMANCE PARAMETERS <table><tbody><tr><td>01</td><td>Effective discharge time</td><td>Minimum : 13 Sec. (Actual : 22 sec approx)</td></tr><tr><td>02</td><td>Bulk range of discharge</td><td>Minimum : 2 meter (Actual : 4 meter approx)</td></tr><tr><td>03</td><td>Percentage of discharge</td><td>Not less than 95% (Actual : 96% approx)</td></tr><tr><td>04</td><td>Fire Rating</td><td>2A:34B</td></tr></tbody></table>																														01	Effective discharge time	Minimum : 13 Sec. (Actual : 22 sec approx)	02	Bulk range of discharge	Minimum : 2 meter (Actual : 4 meter approx)	03	Percentage of discharge	Not less than 95% (Actual : 96% approx)	04	Fire Rating	2A:34B									
01	Effective discharge time	Minimum : 13 Sec. (Actual : 22 sec approx)																																																
02	Bulk range of discharge	Minimum : 2 meter (Actual : 4 meter approx)																																																
03	Percentage of discharge	Not less than 95% (Actual : 96% approx)																																																
04	Fire Rating	2A:34B																																																
MARKING AS PER IS:15683-2006																																																		
16. Extinguishing medium Distilled Water +AFFF Foam (6%) (IS:4989 Complied) 15. Lever Lock PP Plastic 14. Bracket with Screw Mild steel (Powder coated) 13. "C" Clip M.S. 12. Safety pin Holder Rubber/Soft pvc 11. Safety pin S.S. 10. Seal PP Plastic 09. Base PP Plastic 08. Gas Cartridge (60 gm.) ISI Marked - As per IS 4947 07. Discharge Nozzle PVC 06. Discharge hose Rubber Braided EPDM Hose 05. Strainer S.S. 04. Siphone tube (Outlet) Plastic 03. Valve Brass 02. Neck ring M.S.Pipe 01. Body M.S. Sheet Having Maximum Of C=0.25%,P=0.05% and S= 0.05%																																																		
																														00.00.0000.00.00 APP'DA.Shah22.09.16 00.00.0000.00.00 CHK'DNaresh22.09.16 00.00.0000.00.00 DR'NRNG22.09.16 KANEX KANADIA FYR FYTER PVT.LTD (AN ISO-9001-2008 CERTIFIED CO.) PLOT NO- 7, PARAS IND. ESTATE, NEAR GARIBSHA PIR, SIHOR -364 240 (GUJ.) e-mail: tech2@kanexfire.com																				
Sr.No			Item Description			Materials of Constructions			Date		Rev.Dt		Description		XXX		Name		Sign.		Date		TITLE: MECHANICAL FOAM (CARTRIDGE OPERATED) 6 LTR. FIRE EXTINGUISHER			Scale Project		NTS REV.																						
1			2			3			4		5		6		7		8			9			10			SIZE - A4																								