

MODEL NO: KFWCRQ-6																																																																																													
DESIGN DATA																																																																																													
SR.NO.	PARTICULARS	DESCRIPTION																																																																																											
01	Capacity	6 Ltr. ± 5%																																																																																											
02	Temprature range	+5°C to +55°C																																																																																											
03	Service pressure	14 bar																																																																																											
04	Maximum service Pressure	16 bar																																																																																											
05	Pressure test (PT)	35 bar																																																																																											
06	Minimum Burst Pressure Test(PB)	55 bar																																																																																											
PERFORMANCE PARAMETERS																																																																																													
01	Effective discharge time	Minimum : 13 Sec. (Actual : 21 sec approx)																																																																																											
02	Bulk range of discharge	Minimum : 2 meter (Actual : 5 meter approx)																																																																																											
03	Percentage of discharge	Not less than 95% (Actual : 96% approx)																																																																																											
04	Fire Rating	2A																																																																																											
MARKING			AS PER IS:15683-2006																																																																																										
<table><tr><td>16.</td><td>Extinguishing medium</td><td>Distilled Water</td></tr><tr><td>15.</td><td>Lever Lock</td><td>PP Plastic</td></tr><tr><td>14.</td><td>Bracket with Screw</td><td>Mild steel (Powder coated)</td></tr><tr><td>13.</td><td>"C" Clip</td><td>M.S.</td></tr><tr><td>12.</td><td>Safety pin Holder</td><td>Rubber/Soft pvc</td></tr><tr><td>11.</td><td>Safety pin</td><td>S.S.</td></tr><tr><td>10.</td><td>Seal</td><td>PP Plastic</td></tr><tr><td>09.</td><td>Base</td><td>PP Plastic</td></tr><tr><td>08.</td><td>Gas Cartridge (60 gm.)</td><td>ISI Marked - As per IS 4947</td></tr><tr><td>07.</td><td>Discharge Nozzle</td><td>PVC</td></tr><tr><td>06.</td><td>Discharge hose</td><td>Rubber Braided EPDM Hose</td></tr><tr><td>05.</td><td>Strainer</td><td>S.S.</td></tr><tr><td>04.</td><td>Siphone tube (Outlet)</td><td>Plastic</td></tr><tr><td>03.</td><td>Valve</td><td>Brass</td></tr><tr><td>02.</td><td>Neck ring</td><td>M.S.Pipe</td></tr><tr><td>01.</td><td>Body</td><td>M.S. Sheet Having Maximum Of C=0.25%,P=0.05% and S= 0.05%</td></tr></table>			16.	Extinguishing medium	Distilled Water	15.	Lever Lock	PP Plastic	14.	Bracket with Screw	Mild steel (Powder coated)	13.	"C" Clip	M.S.	12.	Safety pin Holder	Rubber/Soft pvc	11.	Safety pin	S.S.	10.	Seal	PP Plastic	09.	Base	PP Plastic	08.	Gas Cartridge (60 gm.)	ISI Marked - As per IS 4947	07.	Discharge Nozzle	PVC	06.	Discharge hose	Rubber Braided EPDM Hose	05.	Strainer	S.S.	04.	Siphone tube (Outlet)	Plastic	03.	Valve	Brass	02.	Neck ring	M.S.Pipe	01.	Body	M.S. Sheet Having Maximum Of C=0.25%,P=0.05% and S= 0.05%	<table><tr><td>00.00.00</td><td>00.00.00</td><td></td><td>APP'D</td><td>A.Shah</td><td></td><td>22.09.16</td></tr><tr><td>00.00.00</td><td>00.00.00</td><td></td><td>CHK'D</td><td>Naresh</td><td></td><td>22.09.16</td></tr><tr><td>00.00.00</td><td>00.00.00</td><td></td><td>DR'N</td><td>RNG</td><td></td><td>22.09.16</td></tr><tr><td>Sr.No</td><td>Item Description</td><td>Materials of Constructions</td><td>Date</td><td>Rev.Dt</td><td>Description</td><td>XXX</td><td>Name</td><td>Sign.</td><td>Date</td><td colspan="2"> KANADIA FYR FYTER PVT.LTD (AN ISO-9001-2008 CERTIFIED CO.) PLOT NO - 7, PARAS IND. ESTATE, NEAR GARIBSHA PIR, SIHOR -364 240.(GUJ.) e-mail: tech2@kanexfire.com</td></tr></table>										00.00.00	00.00.00		APP'D	A.Shah		22.09.16	00.00.00	00.00.00		CHK'D	Naresh		22.09.16	00.00.00	00.00.00		DR'N	RNG		22.09.16	Sr.No	Item Description	Materials of Constructions	Date	Rev.Dt	Description	XXX	Name	Sign.	Date	 KANADIA FYR FYTER PVT.LTD (AN ISO-9001-2008 CERTIFIED CO.) PLOT NO - 7, PARAS IND. ESTATE, NEAR GARIBSHA PIR, SIHOR -364 240.(GUJ.) e-mail: tech2@kanexfire.com	
			16.	Extinguishing medium	Distilled Water																																																																																								
			15.	Lever Lock	PP Plastic																																																																																								
			14.	Bracket with Screw	Mild steel (Powder coated)																																																																																								
			13.	"C" Clip	M.S.																																																																																								
			12.	Safety pin Holder	Rubber/Soft pvc																																																																																								
			11.	Safety pin	S.S.																																																																																								
			10.	Seal	PP Plastic																																																																																								
			09.	Base	PP Plastic																																																																																								
			08.	Gas Cartridge (60 gm.)	ISI Marked - As per IS 4947																																																																																								
07.	Discharge Nozzle	PVC																																																																																											
06.	Discharge hose	Rubber Braided EPDM Hose																																																																																											
05.	Strainer	S.S.																																																																																											
04.	Siphone tube (Outlet)	Plastic																																																																																											
03.	Valve	Brass																																																																																											
02.	Neck ring	M.S.Pipe																																																																																											
01.	Body	M.S. Sheet Having Maximum Of C=0.25%,P=0.05% and S= 0.05%																																																																																											
00.00.00	00.00.00		APP'D	A.Shah		22.09.16																																																																																							
00.00.00	00.00.00		CHK'D	Naresh		22.09.16																																																																																							
00.00.00	00.00.00		DR'N	RNG		22.09.16																																																																																							
Sr.No	Item Description	Materials of Constructions	Date	Rev.Dt	Description	XXX	Name	Sign.	Date	 KANADIA FYR FYTER PVT.LTD (AN ISO-9001-2008 CERTIFIED CO.) PLOT NO - 7, PARAS IND. ESTATE, NEAR GARIBSHA PIR, SIHOR -364 240.(GUJ.) e-mail: tech2@kanexfire.com																																																																																			