



KANEX[®]

Shaping the future of Fire Protection



PRODUCT CATALOG

www.kanexfire.com



WHERE TO USE?

- An extinguisher is a First-aid device which is used against the critical situations of fire only. There is no chance for testing the device while fire is going on, that's why the device must be totally reliable and user friendly.
- When it comes to application, Fire equipment needs to be identifiable, handy and appropriate for the property it is intended to protect.
- But good fire protection is about more than just having the right devices in the right places, also requires rigorous monitoring to ensure that it will perform effectively when needed.
- Everyone should be familiar with the picture symbols which identify the types of fires on which they may be used. As listed below.
- The symbol diagonal red slashes indicates a potential danger if the extinguisher is used on that particular type of fire.
- Absence of a type symbol means only that the extinguisher is not recommended as particularly effective for that classification of fire.

| | | | |
|--|--|--|--|
| | | | Suitable for Class B and Class C fires but not for Class A |
| | | | Suitable for Class A fires but not for Class B or Class C |
| | | | Suitable for Class A and Class B fires but not for Class C |

HOW TO USE?

- "KANEX" provides you a valuable user manual which contains very much needed information like how to use, install and maintenance of an extinguisher.
- The Label affixed on extinguisher body contains specific information of "HOW TO OPERATE" the particular extinguisher.
- The label instruction will change according to size and type of extinguisher.
- Every one should be aware of Instructions provided on Extinguishers.





AUTOMATIC TYPE MODULAR **FIRE EXTINGUISHER SERIES** →

KANEX AUTOMATIC FIRE EXTINGUISHERS which keeps guard and extinguishes fire quickly and efficiently. In the event of fire, Kanex Modular type extinguishers activate automatically, spraying the extinguishing agent with maximum force, ensuring that the fire is brought under control rapidly and efficiently

Ideal Use



Switch gears



Office



Sensitive data storage



Aircraft's



Boats



Laboratories

AUTOMATIC TYPE POWDER MODULAR EXTINGUISHER

FEATURES

- Hydraulically tested as per standard and passed through anti-corrosive treatment
- An Automatic Detection and Suppression System together in a single unit quite unlike any other system available in the market
- Automatic round-the-clock protection
- Automatic operation, hence no human involvement, reducing the chances of injury and accidents to virtually zero.
- Proves to be the most economical when compared to other systems
- Reusable cylinder as it is not based on aerosol technology. Hence, most economical
- Non-Freezing & long lasting
- Provides securities in case of emergencies and power failure without power backup
- Rechargeable and easy to service
- Extinguishing medium is Mono Ammonium Phosphate powder



Class A



Class B



Class C



Electrical

PERFORMANCE DATA

| MODEL (MAP 50% POWDER) | KMPRQ-2-50% | KMPRQ-5-50% | KMPRQ-10-50% | KMPRQ-15-50% |
|---------------------------|-------------------------|-------------------------|-----------------------|-----------------------|
| MODEL (MAP 90% POWDER)* | KMPRQ-2-90% | KMPRQ-5-90% | KMPRQ-10-90% | KMPRQ-15-90% |
| Capacity | 2 kg | 5 kg | 10 kg | 15 kg |
| Design | Ceiling Mounted | Ceiling Mounted | Ceiling Mounted | Ceiling Mounted |
| Height (Approx) | 380 mm | 375 mm | 405 mm | 425 mm |
| Diameter (Approx) | 150 ± 10 mm | 230 ± 10 mm | 300 ± 10 mm | 400 ± 10 mm |
| Average Discharge time | 4-5 Sec | 6-8 Sec | 10-15 Sec | 15-20 Sec |
| Hanging height above risk | 1.5 Mtr | 1.5 to 2 Mtr | 1.75 to 2.25 Mtr | 2 to 3 Mtr |
| Area Protection | 1 to 1.5 m ² | 2 to 2.5 m ² | 4 to 6 m ² | 5 to 6 m ² |
| Volume Protection | 3 m ³ | 7 m ³ | 12 m ³ | 17 m ³ |
| Average % Discharge | 99% | 99% | 99% | 99% |
| Operating Temperature | -30 °C to +60 °C | | | |
| Service / Test Pressure | 15 / 35 bar | | | |
| Expelling Agent | Nitrogen (UHP grade) | | | |
| Empty Weight (Approx.) | 1.5 / 3.5 / 3.8 kg | 2.6 / 7.6 / 8 kg | 4.1 / 14.1 / 14.5 kg | 6.4 / 21.4 / 22 kg |
| Mounting Bracket | Ceiling mounting stand | | | |

* HQ Series available with UL Listed MAP-90% Powder also

Designed, Manufactured & Marketed by:
KANADIA FYR FYTER PVT. LTD.
An Iso 9001:2015 certified company

HEAD OFFICE:

Office No.502, 5th floor, A wing,
Damji Shamji Corporate Square, Ghatkopar - Andheri Link Road,
Laxmi Nagar, Ghatkopar (E) - 400 075

WORKS:

Kanadia Fyr Fyter Pvt.Ltd.
Plot No.7-8 Paras Industrial, Estate Nr.Garibsha Plr,
Sihor-364240, Dist. Bhavnagar(Guj)

marketing@kanexfire.com | www.kanexfire.com
Presence at - PAN INDIA