



## CO<sub>2</sub> TYPE TROLLEY MOUNTED FIRE EXTINGUISHER

KANEX CO<sub>2</sub> TROLLEY MOUNTED fire extinguishers are characterized by their high performance for fires involving an electrical risk like computers, office equipment and generators etc. CO<sub>2</sub> is non-conductive, clean and safe, ensuring minimal damage to electrical equipment and furnishings.

**Ideal Use:** Chemical Manufacturing Plant, Oil Ring, Rail Yards, Warehouses, Construction sites, Parking garages, Airport, Electrical substation and Large laboratories.



Class B



Class C



Electrical



### FEATURES

- Carbon Di Oxide is Colorless, Odorless, Non Toxic and provides rapid knockdown of industrial fires.
- BIS Approved and ISI marked
- CCOE/PESO approved cylinder body and confirms to IS:7285
- High grade enamel painted externally with PO Red finish
- Wheel Operated Controlled discharge
- High pressure Brass valve confirms to IS:3224 which provided with pressure relief disc
- Rechargeable and easy to service
- Non conductive agent for electrical use without risk to operator
- CO<sub>2</sub> gas disappears quickly leaving no residue
- Wire Braided Hose & Flat Horn with Diffuser Nozzle for dispersed discharge of Carbon Di Oxide
- Conformity standard IS 16018:2012

### PERFORMANCE DATA

MODEL (WHEEL TYPE VALVE)	KFCRQ-6.5	KFCRQ-9	KFCRQ-22.5
Capacity	6.5 kg	9 kg	22.5 kg
Design	Hose & Horn	Hose & Horn	Hose & Horn
Fire Rating	55B	55B	89B
Height (Approx)	960 mm	1250 mm	1155 mm
Diameter (Approx)	140 ± 10 mm	140 ± 10 mm	232 ± 10 mm
Average Discharge time	20 Sec	30 Sec	47 Sec
Average Range of throw	3 m	3 m	4 m
Average % Discharge	96%	96%	96%
Operating Temperature	-30 °C to +55 °C		
Service/Max. service/Test Pressure	60 / 105 / 250 bar		
Empty Weight (Approx.)	16.5 or 18.5 kg	25 or 26 kg	61.5 or 63.5 kg
Full Weight (Approx.)	23 or 25 kg	34 or 36 kg	84 or 86 kg
Shipping Weight (Approx.)	24 or 26 kg	35 or 37 kg	85 or 87 kg
Packing Standard	Corrugated paper & Jute Bags		
Approval	BIS		