

FOAM & WATER TYPE STORED PRESSURE FIRE EXTINGUISHER

KANEX STORED PRESSURE Foam and Water fire extinguisher are ideal for fires involving volatile liquids and freely burning materials such as paper, cloth, wood and furniture.
Note: Mechanical Foam & water extinguishers are not suitable for fires involving electrical risk.

Ideal Use: Plywood companies (WATER), Petrol Stations (FOAM), Restaurants, etc.

- Water Type Suitable for Class A Fire Risk
- Foam Type Suitable for Class A and Class B Fire Risk



Class A



Class A



Class B



Caution :
Don't use on Electrical Fire.

FEATURES

- AFFF (Aqueous Film Forming Foam) fights against Class A and Class B fires
- Water type extinguisher effectively works on class A fires
- BIS Approved and ISI marked
- High quality Pure Polyester (PP) powder coating (UV Resistant)
- Air aspirated nozzle to provide high fire rating in case of Foam extinguisher
- Brass chrome plated valve with simple squeeze operation and controllable discharge
- Unique Gauge Testing System (UGTS) mechanism
- Hydraulically tested as per standard and passed through anti-corrosive treatment
- Easy to maintain, recharge & service
- Large loop Stainless steel Pull pin
- EPDM Rubber braided hose is far more flexible than the PVC braided
- Conformity standard IS: 15683:2018

PERFORMANCE DATA

MODEL	FOAM		WATER	
	KFMSRQ-6	KFMSRQ-9	KFWSRQ-6	KFWSRQ-9
Capacity	6 Ltr	9 Ltr	6 Ltr	9 Ltr
Design	Hose & Nozzle	Hose & Nozzle	Hose & Nozzle	Hose & Nozzle
Fire Rating	3A : 89B*	4A : 144B	2A*	3A
Height (Approx.)	530 mm	575 mm	530 mm	575 mm
Diameter (Approx.)	150 ± 5 mm	180 ± 5 mm	150 ± 5 mm	180 ± 5 mm
Average Discharge time	22 Sec	35 Sec	22 Sec	35 Sec
Average Range of throw	6 m	6 m	5 m	6 m
Average % Discharge	96%	97%	96%	97%
Operating Temperature	+5 °C to +60 °C			
Service/Max. service/Test Pressure	15 / 18 / 35 bar			
Expelling Agent	Nitrogen (UHP Grade)			
Empty Weight (Approx.)	3.6 kg	4.9 kg	3.6 kg	4.9 kg
Full Weight (Approx.)	9.6 kg	13.9 kg	9.6 kg	13.9 kg
Shipping Weight (Approx.)	10 kg	14.4 kg	10 kg	14.4 kg
Packing Standard	2 in 1 - 22.5"X6.75"X14.10"	1 in 1 - 24.75"X8"X8"	2 in 1 - 22.5"X6.75"X14.10"	1 in 1 - 24.75"X8"X8"
Mounting Bracket	Wall Bracket			
Approvals	—	BIS	—	BIS

* Indicates factory tested