



FOAM AND WATER STORED PRESSURE FIRE EXTINGUISHER WITH SS BODY

KANEX AR-AFFF FOAM SMOOTH FINISH SS BODY STORED PRESSURE extinguishers provides a fast, power full means of tackling flammable liquids. The foam forms a seal over the surface to prevent re-ignition. Ideal for multi-risk usage and also applicable against Class 'A' hazards such as wood, cloth, trash and other materials that leave an ash.

Ideal Use: Plywood industries (WATER) Petrol Stations (FOAM) , Restaurants, etc.

Caution : Don't use on Electrical Fire.

- Water Type Suitable for Class A Fire Risk
- Foam Type Suitable for Class A and Class B Fire Risk



Class A



Class A



Class B



FIRE RATINGS

	Capacity	BIS Rating	BS EN Rating
M FOAM	6 Ltr	3A:89B*	13A:89B*
	9 Ltr	4A:144B	27A:183B*
WATER	6 Ltr	2A*	13A*
	9 Ltr	4A	27A*

HQ SERIES FEATURES



AR-AFF agent conforms to IS:4989 (Part-II) capable of fighting against Class A and B fires



HQ series products are designed to achieve the best Fire Rating Refer the above table



Unique Gauge Testing System (UGTS) Mechanism



CE marked, brass chrome plated valve with Controlled discharge mechanism and Large loop Stainless steel Pull pin



EPDM Rubber braided hose is far more flexible than the PVC braided hoses and also far less prone to cracks



Hydraulically tested as per standard requirements



Smooth finish stainless steel body to give aesthetic impression



Helium Leak Detection tested for leakage, leak rate up to 1×10^{-8} mbar.l/sec.



Easy to maintain, recharge & service



BIS Approved (IS 15683:2018), ISI marked and CE Certified

PERFORMANCE DATA

MODEL	FOAM		WATER	
	KFMSSHQ-6-AR	KFMSSHQ-9-AR	KFWSSHQ-6	KFWSSHQ-9
Capacity	6 Ltr	9 Ltr	6 Ltr	9 Ltr
Design	Hose & Nozzle	Hose & Nozzle	Hose & Nozzle	Hose & Nozzle
Fire Rating	3A : 89B*	4A : 144B	2A*	4A
Height (Approx.)	550 mm	610 mm	550 mm	610 mm
Diameter (Approx.)	150 ± 5 mm	180 ± 5 mm	150 ± 5 mm	180 ± 5 mm
Average Discharge time	22 Sec	35 Sec	22 Sec	35 Sec
Average Range of throw	6 m	6 m	5 m	6 m
Average % Discharge	96%	97%	96%	97%
Operating Temperature	+5 °C to +60 °C			
Service/Max. service/Test Pressure	15 / 18 / 35 bar			
Expelling Agent	Nitrogen (UHP Grade)			
Empty Weight (Approx.)	2.8 kg	3.6 kg	2.8 kg	3.6 kg
Full Weight (Approx.)	8.8 kg	12.6 kg	8.8 kg	12.6 kg
Shipping Weight (Approx.)	9.2 kg	13.1 kg	9.2 kg	13.1 kg
Packing Standard	2 in 1 - 22.5"X6.75"X14.10"	1 in 1 - 24.75"X8"X8"	2 in 1 - 22.5"X6.75"X14.10"	1 in 1 - 24.75"X8"X8"
Mounting Bracket	Wall Bracket			
Approvals	CE	BIS & CE	CE	BIS & CE

* Indicates factory tested