



Product Short description for Enquiry RQ Series ABC Dry Powder MAP 90% Cartridge Operated Fire Extinguishers

ABC DRY POWDER MAP 90% (CARTRIDGE OPERATED) 4 KG 2A:34B FIRE EXTINGUISHER IS:15683

RQ	KFD4 (MAP 90%)-(R)	"KANEX" DCP type Fire extinguisher cap. 4 Kg. filled with Mono Ammonium Phosphate Powder 50% confirm to IS 14609 Applicable fire classes A, B & C, Gross Weight 7.3 Kg, empty Weight 3.3 Kg, Can Height 510mm, Diameter 140 ± 10mm, CO2 gas Cartridge of 120 gm confirms to IS 4947, Controllable discharge mechanism with EPDM Hose & Open Nozzle, Discharge Time 15 Sec, Jet Range 4 Meters, Average Discharge is 90%, Fire rating: A Rating 2A & B Rating 34B , Can Construction : Deep drawn & MIG Welding technology, CE Marked Brass forged Squeeze grip type valves with Auto safety release at 24 bar and safety Pin is of SS material, Internal Coating - Epoxy Powder coating, External Coating - Pure Polyester Powder coating and Welding Procedure approved by TPI with 6 G certification . Sheet metal thickness: 1.8 mm, Confirms to IS 15683:2006 and ISI Marked, 5 Years Warranty.
----	--------------------	---

ABC DRY POWDER MAP 90% (CARTRIDGE OPERATED) 6 KG 3A:55B FIRE EXTINGUISHER IS:15683

RQ	KFD6 (MAP 90%)-(R)	"KANEX" DCP type Fire extinguisher cap. 6 Kg. filled with Mono Ammonium Phosphate Powder 50% confirm to IS 14609 Applicable fire classes AB & C, Gross Weight 10.3 Kg, empty Weight 4.3 Kg, Can Height 540mm, Diameter 150 ± 10mm, CO2 gas Cartridge of 120 gm confirms to IS 4947, Controllable discharge mechanism with EPDM Hose & Open Nozzle, Discharge Time 20 Sec, Jet Range 4.5 Meters, Average Discharge is 90%, Fire rating: A Rating 3A & 55B Rating 55B , Can Construction : Deep drawn & MIG Welding technology, CE Marked Brass forged Squeeze grip type valves with Auto safety release at 24 bar (About 950 gm. wt.) and safety Pin is of SS material, Internal Coating - Epoxy Powder coating, External Coating - Pure Polyester Powder coating (UV Resistant) and Welding Procedure approved by TPI with 6 G certification . Sheet metal thickness : 1.8 mm, Confirms to IS 15683:2006 and ISI Marked, 5 Years Warranty.
----	--------------------	--

ABC DRY POWDER-MAP 90% (CARTRIDGE OPERATED) 9 KG 4A:89B FIRE EXTINGUISHER IS:15683

RQ	KFD9 (MAP 90%)-(R)	"KANEX" DCP type Fire extinguisher cap. 9 Kg. filled with with Mono Ammonium Phosphate Powder 50% confirm to IS 14609 Applicable fire classes A, B & C, Gross Weight 15.3 Kg, empty Weight 6.3 Kg, Can Height 585mm, Diameter 180 ± 10mm, CO2 gas Cartridge of 200 gm confirms to IS 4947, Controllable discharge mechanism with EPDM Hose & Open Nozzle, Discharge Time 30 Sec, Jet Range 5 Meters, Average Discharge is 90%, Fire rating: A Rating 4A & B Rating 89B , Can Construction : Deep drawn & MIG Welding technology, CE Marked Brass forged Squeeze grip type valves with Auto safety release at 24 bar (About 950 gm. wt.) and safety Pin is of SS material, Internal Coating - Epoxy Powder coating, External Coating - Pure Polyester Powder coating (UV Resistant) and Welding Procedure approved by TPI with 6 G certification . Sheet metal thickness : 2.0 mm, Confirms to IS 15683:2006 and ISI Marked, 5 Years Warranty.
----	--------------------	---