



## Product Short description for Enquiry HQ Series ABC Dry Powder MAP 90% Stored Pressure Fire Extinguishers

### ABC DRY POWDER MAP-90% ( STORED PRESSURE ) 1 KG 1A:13B FIRE EXTINGUISHER IS:15683

HQ	KFA-1-90%	<b>KANEX ABC Type Fire Extinguisher Cap. 1 kg Filled with Mono Ammonium Phosphate Powder 90% confirms to IS 14609</b> , Stored Pressure Type, <b>UGTS Pressure Gauge</b> , Gross Weight 2 Kg, Empty Weight 1 Kg, Can Height 325mm, Diameter 86 ± 10mm, Discharge Time 8 Sec, Controllable discharge mechanism, Jet Range 2 Meters, Average Discharge is 90%, applicable on Class A,B & C and electrically started Fire, <b>A Rating- 1A, B Rating 13B</b> , Can Construction : Deep drawn & CO2 Mig welded, <b>CE Marked Valve with inbuilt NRV &amp; Safety Release Provision</b> , Internal Coating - Epoxy Powder coating, <b>External Coating - Pure Polyester Powder coating (UV Resistant)</b> , Brass forged valves with safety Pin is of SS material, and <b>Welding Procedure approved by TPI with 6 G certification</b> , Sheet metal thickness : 1.6 mm, <b>Helium Leak Detection Tested, ISI Approved IS 15683:2006 and CE Certified</b> , 5 Years Warranty.
----	-----------	--

### ABC DRY POWDER MAP-90% (STORED PRESSURE ) 2 KG 1A:21B FIRE EXTINGUISHER IS:15683

HQ	KFA-2-90%	<b>KANEX ABC Type Fire Extinguisher Cap. 2 kg Filled with Mono Ammonium Phosphate Powder 90% confirms to IS 14609</b> , Stored Pressure Type, <b>UGTS Pressure Gauge</b> , Gross Weight 3.4 Kg, Empty Weight 1.4 Kg, Can Height 380mm, Diameter 106 ± 10mm, Discharge Time 8 Sec, Controllable discharge mechanism, Jet Range 2 Meters, Average Discharge is 90%, applicable on Class A,B & C and electrically started Fire, <b>A Rating- 1A, B Rating 21B</b> , Can Construction : Deep drawn & CO2 Mig welded, <b>CE Marked Valve with inbuilt NRV &amp; Safety Release Provision</b> , Internal Coating - Epoxy Powder coating, <b>External Coating - Pure Polyester Powder coating (UV Resistant)</b> , Brass forged valves with safety Pin is of SS material, and <b>Welding Procedure approved by TPI with 6 G certification</b> , Sheet metal thickness : 1.6 mm, <b>Helium Leak Detection Tested, ISI Approved IS 15683:2006 and CE Certified</b> , 5 Years Warranty.
----	-----------	---

### ABC DRY POWDER MAP-90% ( STORED PRESSURE ) 4 KG 2A:21B FIRE EXTINGUISHER IS:15683

HQ	KFA-4-90%	<b>KANEX ABC Type Fire Extinguisher Cap. 4 kg Filled with Mono Ammonium Phosphate Powder 90% confirms to IS 14609</b> , Stored Pressure Type, <b>UGTS Pressure Gauge</b> , Gross Weight 6.6 Kg, Empty Weight 2.6 Kg, Can Height 490mm, Diameter 140 ± 10mm, Discharge Time 18 Sec, Controllable discharge mechanism, Jet Range 3 Meters, Average Discharge is 90%, applicable on Class A,B & C and electrically started Fire, <b>A Rating- 2A, B Rating 21B</b> , Can Construction : Deep drawn & CO2 Mig welded, <b>CE Marked Valve with inbuilt NRV &amp; Safety Release Provision</b> , <b>EPDM Rubber Hose with both end Aluminum clamped, Plastic base provided</b> , Internal Coating - Epoxy Powder coating, <b>External Coating - Pure Polyester Powder coating (UV Resistant)</b> , Brass forged valves with safety Pin is of SS material, and <b>Welding Procedure approved by TPI with 6 G certification</b> , Sheet metal thickness : 1.8 mm, <b>Helium Leak Detection Tested, ISI Approved IS 15683:2006 and CE Certified</b> , 5 Years Warranty.
----	-----------	--



## Product Short description for Enquiry

### HQ Series ABC Dry Powder MAP 90% Stored Pressure Fire Extinguishers

#### ABC DRY POWDER MAP-90% (STORED PRESSURE ) 6 KG 3A:21B FIRE EXTINGUISHER IS:15683

HQ	KFA-6-90%	<b>KANEX ABC Type Fire Extinguisher Cap. 6 kg Filled with Mono Ammonium Phosphate Powder 90% confirms to IS 14609</b> , Stored Pressure Type, <b>UGTS Pressure Gauge</b> , Gross Weight 8.9 Kg, Empty Weight 2.9 Kg, Can Height 530 mm, Diameter 150 ± 10mm, Discharge Time 24 Sec, Controllable discharge mechanism, Jet Range 5 Meters, Average Discharge is 90%, applicable on Class A,B & C and electrically started Fire, <b>A Rating- 3A, B Rating 21B</b> , Can Construction : Deep drawn & CO2 Mig welded, CE Marked Valve with inbuilt NRV & Safety Release Provision, <b>EPDM Rubber Hose with both end Aluminum clamped</b> , Plastic base provided, Internal Coating - Epoxy Powder coating, <b>External Coating - Pure Polyester Powder coating (UV Resistant)</b> , Brass forged valves with safety Pin is of SS material, and <b>Welding Procedure approved by TPI with 6 G certification</b> , Sheet metal thickness : 1.8 mm, <b>Helium Leak Detection Tested, ISI Approved IS 15683:2006 and CE Certified</b> , 5 Years Warranty.
----	-----------	---

#### ABC DRY POWDER MAP-90% (STORED PRESSURE ) 9 KG 4A:89B FIRE EXTINGUISHER IS:15683

HQ	KFA-9-90%	<b>"KANEX" ABC Type Fire Extinguisher Cap. 9 kg Filled with Mono Ammonium Phosphate Powder 90% confirms to IS 14609</b> , Stored Pressure Type, <b>UGTS Pressure Gauge</b> , Gross Weight 13.3 Kg, Empty Weight 4.3 Kg, Can Height 575 mm, Diameter 180 ± 10mm, Discharge Time 31 Sec, Controllable discharge mechanism, Jet Range 6 Meters, Average Discharge is 90%, applicable on Class A,B & C and electrically started Fire, <b>A Rating- 4A, B Rating 89B</b> , Can Construction : Deep drawn & CO2 Mig welded, <b>CE Marked Valve with inbuilt NRV &amp; Safety Release Provision</b> , <b>EPDM Rubber Hose with both end Aluminum clamped, Plastic base provided</b> , Internal Coating - Epoxy Powder coating, <b>External Coating - Pure Polyester Powder coating (UV Resistant)</b> , Brass forged valves with safety Pin is of SS material, and <b>Welding Procedure approved by TPI with 6 G certification</b> , Sheet metal thickness : 2.0 mm, <b>Helium Leak Detection Tested, ISI Approved IS 15683:2006 and CE Certified</b> , 5 Years Warranty.
----	-----------	--