



Product Short description for Enquiry
RQ Series ABC Dry Powder MAP Stored Pressure Fire Extinguishers

ABC DRY POWDER MAP-50% (STORED PRESSURE) 1 KG 8B FIRE EXTINGUISHER IS:15683

ABC DRY POWDER MAP- 50% (STORED PRESSURE) 1 KG 8B FIRE EXTINGUISHER IS:15683	RQ	KFA-1-50%	KANEX ABC Dry Powder Type Fire Extinguisher Cap. 1 kg Filled with Mono Ammonium Phosphate Powder 50% confirms to IS 14609 , Stored Pressure Type, UGTS Pressure Gauge , Gross Weight 2 Kg, Empty Weight 1 Kg, Can Height 325mm, Diameter 86 ± 10mm, Discharge Time 8 Sec, Controllable discharge mechanism, Jet Range 2 Meters, Average Discharge is 90%, applicable on Class A,B & C and electrically started Fire, B Rating 8B , Can Construction : Deep drawn & CO2 Mig welded, Internal Coating - Epoxy Powder coating, External Coating - Pure Polyester Powder coating (UV Resistant) , Brass forged valves with safety Pin is of SS material, Sheet metal thickness : 1.6 mm, ISI Approved IS 15683:2006.
---	-----------	------------------	--

ABC DRY POWDER MAP-50% (STORED PRESSURE) 2 KG 8B FIRE EXTINGUISHER IS:15683

ABC DRY POWDER MAP- 50% (STORED PRESSURE) 2 KG 8B FIRE EXTINGUISHER IS:15683	RQ	KFA-2-50%	KANEX ABC Type Fire Extinguisher Cap. 2 kg Filled with Mono Ammonium Phosphate Powder 50% confirms to IS 14609 , Stored Pressure Type, UGTS Pressure Gauge , Gross Weight 3.4 Kg, Empty Weight 1.4 Kg, Can Height 380mm, Diameter 106 ± 10mm, Discharge Time 8 Sec, Controllable discharge mechanism, Jet Range 2 Meters, Average Discharge is 90%, applicable on Class A,B & C and electrically started Fire, B Rating 8B , Can Construction : Deep drawn & CO2 Mig welded, Internal Coating - Epoxy Powder coating, External Coating - Pure Polyester Powder coating (UV Resistant) , Brass forged valves with safety Pin is of SS material, Sheet metal thickness : 1.6 mm, ISI Approved IS 15683:2006.
---	-----------	------------------	--

ABC DRY POWDER MAP-50% (STORED PRESSURE) 4 KG 2A:21B FIRE EXTINGUISHER IS:15683

ABC DRY POWDER MAP- 50% (STORED PRESSURE) 4 KG 2A:21B FIRE EXTINGUISHER IS:15683	RQ	KFA-4-50%	KANEX ABC Type Fire Extinguisher Cap. 4 kg Filled with Mono Ammonium Phosphate Powder 50% confirms to IS 14609 , Stored Pressure Type, UGTS Pressure Gauge , Gross Weight 6.6 Kg, Empty Weight 2.6 Kg, Can Height 490mm, Diameter 140 ± 10mm, Discharge Time 18 Sec, Controllable discharge mechanism, Jet Range 3 Meters, Average Discharge is 90%, applicable on Class A,B & C and electrically started Fire, A Rating- 2A, B Rating 21B , Can Construction : Deep drawn & CO2 Mig welded, EPDM Rubber Hose with both end Aluminum clamped , Internal Coating - Epoxy Powder coating, External Coating - Pure Polyester Powder coating (UV Resistant) , Brass forged valves with safety Pin is of SS material, Sheet metal thickness : 1.8 mm, ISI Approved IS 15683:2006.
---	-----------	------------------	---



Product Short description for Enquiry
RQ Series ABC Dry Powder MAP Stored Pressure Fire Extinguishers

ABC DRY POWDER MAP-50% (STORED PRESSURE) 6 KG 3A:21B FIRE EXTINGUISHER IS:15683

ABC DRY POWDER MAP- 50% (STORED PRESSURE) 6 KG 3A:21B FIRE EXTINGUISHER IS:15683	RQ	KFA-6-50%	KANEX ABC Type Fire Extinguisher Cap. 6 kg Filled with Mono Ammonium Phosphate Powder 50% confirms to IS 14609 , Stored Pressure Type, UGTS Pressure Gauge , Gross Weight 8.9 Kg, Empty Weight 2.9 Kg, Can Height 530 mm, Diameter 150 ± 10mm, Discharge Time 24 Sec, Controllable discharge mechanism, Jet Range 5 Meters, Average Discharge is 90%, applicable on Class A,B & C and electrically started Fire, A Rating- 3A, B Rating 21B , Can Construction : Deep drawn & CO2 Mig welded, EPDM Rubber Hose with both end Aluminum clamped , Internal Coating - Epoxy Powder coating, External Coating - Pure Polyester Powder coating (UV Resistant) , Brass forged valves with safety Pin is of SS material, Sheet metal thickness : 1.8 mm, ISI Approved IS 15683:2006.
---	-----------	------------------	--

ABC DRY POWDER MAP-50% (STORED PRESSURE) 9 KG 3A:21B FIRE EXTINGUISHER IS:15683

ABC DRY POWDER MAP- 50% (STORED PRESSURE) 9 KG 3A:21B FIRE EXTINGUISHER IS:15683	RQ	KFA-9-50%	KANEX ABC Type Fire Extinguisher Cap. 9 kg Filled with Mono Ammonium Phosphate Powder 50% confirms to IS 14609 , Stored Pressure Type, UGTS Pressure Gauge , Gross Weight 13.3 Kg, Empty Weight 4.3 Kg, Can Height 575 mm, Diameter 180 ± 10mm, Discharge Time 31 Sec, Controllable discharge mechanism, Jet Range 6 Meters, Average Discharge is 90%, applicable on Class A,B & C and electrically started Fire, A Rating- 3A, B Rating 21B , Can Construction : Deep drawn & CO2 Mig welded, EPDM Rubber Hose with both end Aluminum clamped , Internal Coating - Epoxy Powder coating, External Coating - Pure Polyester Powder coating (UV Resistant) , Brass forged valves with safety Pin is of SS material, Sheet metal thickness : 2.0 mm, ISI Approved IS 15683:2006.
---	-----------	------------------	---

ABC DRY POWDER MAP-90% (STORED PRESSURE) 1 KG 1A:13B FIRE EXTINGUISHER IS:15683

ABC DRY POWDER MAP- 90% (STORED PRESSURE) 1 KG 1A:13B FIRE EXTINGUISHER IS:15683	HQ	KFA-1-90% (R)	KANEX ABC Type Fire Extinguisher Cap. 1 kg Filled with Mono Ammonium Phosphate Powder 90% confirms to IS 14609 , Stored Pressure Type, UGTS Pressure Gauge , Gross Weight 2 Kg, Empty Weight 1 Kg, Can Height 325mm, Diameter 86 ± 10mm, Discharge Time 8 Sec, Controllable discharge mechanism, Jet Range 2 Meters, Average Discharge is 90%, applicable on Class A,B & C and electrically started Fire, A Rating- 1A, B Rating 13B , Can Construction : Deep drawn & CO2 Mig welded, CE Marked Valve with inbuilt NRV & Safety Release Provision , Internal Coating - Epoxy Powder coating, External Coating - Pure Polyester Powder coating (UV Resistant) , Brass forged valves with safety Pin is of SS material, and Welding Procedure approved by TPI with 6 G certification , Sheet metal thickness : 1.6 mm, Helium Leak Detection Tested, ISI Approved IS 15683:2006 and CE Certified, 5 Years Warranty.
---	-----------	--------------------------	---



Product Short description for Enquiry
RQ Series ABC Dry Powder MAP Stored Pressure Fire Extinguishers

ABC DRY POWDER MAP-90% (STORED PRESSURE) 2 KG 1A:21B FIRE EXTINGUISHER IS:15683

ABC DRY POWDER MAP- 90% (STORED PRESSURE) 2 KG 1A:21B FIRE EXTINGUISHER IS:15683	HQ	KFA-2-90% (R)	KANEX ABC Type Fire Extinguisher Cap. 2 kg Filled with Mono Ammonium Phosphate Powder 90% confirms to IS 14609 , Stored Pressure Type, UGTS Pressure Gauge , Gross Weight 3.4 Kg, Empty Weight 1.4 Kg, Can Height 380mm, Diameter 106 ± 10mm, Discharge Time 8 Sec, Controllable discharge mechanism, Jet Range 2 Meters, Average Discharge is 90%, applicable on Class A,B & C and electrically started Fire, A Rating- 1A, B Rating 21B , Can Construction : Deep drawn & CO2 Mig welded, CE Marked Valve with inbuilt NRV & Safety Release Provision , Internal Coating - Epoxy Powder coating, External Coating - Pure Polyester Powder coating (UV Resistant) , Brass forged valves with safety Pin is of SS material, and Welding Procedure approved by TPI with 6 G certification , Sheet metal thickness : 1.6 mm, Helium Leak Detection Tested, ISI Approved IS 15683:2006 and CE Certified, 5 Years Warranty.
--	-----------	--------------------------	--

ABC DRY POWDER MAP-90% (STORED PRESSURE) 4 KG 2A:21B FIRE EXTINGUISHER IS:15683

ABC DRY POWDER MAP- 90% (STORED PRESSURE) 4 KG 2A:21B FIRE EXTINGUISHER IS:15683	HQ	KFA-4-90% (R)	KANEX ABC Type Fire Extinguisher Cap. 4 kg Filled with Mono Ammonium Phosphate Powder 90% confirms to IS 14609 , Stored Pressure Type, UGTS Pressure Gauge , Gross Weight 6.6 Kg, Empty Weight 2.6 Kg, Can Height 490mm, Diameter 140 ± 10mm, Discharge Time 18 Sec, Controllable discharge mechanism, Jet Range 3 Meters, Average Discharge is 90%, applicable on Class A,B & C and electrically started Fire, A Rating- 2A, B Rating 21B , Can Construction : Deep drawn & CO2 Mig welded, CE Marked Valve with inbuilt NRV & Safety Release Provision, EPDM Rubber Hose with both end Aluminum clamped, Plastic base provided , Internal Coating - Epoxy Powder coating, External Coating - Pure Polyester Powder coating (UV Resistant) , Brass forged valves with safety Pin is of SS material, and Welding Procedure approved by TPI with 6 G certification , Sheet metal thickness : 1.8 mm, Helium Leak Detection Tested, ISI Approved IS 15683:2006 and CE Certified, 5 Years Warranty.
---	-----------	--------------------------	---



Product Short description for Enquiry
RQ Series ABC Dry Powder MAP Stored Pressure Fire Extinguishers

ABC DRY POWDER MAP-90% (STORED PRESSURE) 6 KG 3A:21B FIRE EXTINGUISHER IS:15683

ABC DRY POWDER MAP- 90% (STORED PRESSURE) 6 KG 3A:21B FIRE EXTINGUISHER IS:15683	HQ	KFA-6-90% (R)	KANEX ABC Type Fire Extinguisher Cap. 6 kg Filled with Mono Ammonium Phosphate Powder 90% confirms to IS 14609 , Stored Pressure Type, UGTS Pressure Gauge , Gross Weight 8.9 Kg, Empty Weight 2.9 Kg, Can Height 530 mm, Diameter 150 ± 10mm, Discharge Time 24 Sec, Controllable discharge mechanism, Jet Range 5 Meters, Average Discharge is 90%, applicable on Class A,B & C and electrically started Fire, A Rating- 3A, B Rating 21B , Can Construction : Deep drawn & CO2 Mig welded, CE Marked Valve with inbuilt NRV & Safety Release Provision, EPDM Rubber Hose with both end Aluminum clamped , Plastic base provided, Internal Coating - Epoxy Powder coating, External Coating - Pure Polyester Powder coating (UV Resistant) , Brass forged valves with safety Pin is of SS material, and Welding Procedure approved by TPI with 6 G certification , Sheet metal thickness : 1.8 mm, Helium Leak Detection Tested, ISI Approved IS 15683:2006 and CE Certified , 5 Years Warranty.
--	-----------	--------------------------	---

ABC DRY POWDER MAP-90% (STORED PRESSURE) 9 KG 4A:89B FIRE EXTINGUISHER IS:15683

ABC DRY POWDER MAP- 90% (STORED PRESSURE) 9 KG 4A:89B FIRE EXTINGUISHER IS:15683	HQ	KFA-9-90% (R)	"KANEX" ABC Type Fire Extinguisher Cap. 9 kg Filled with Mono Ammonium Phosphate Powder 90% confirms to IS 14609 , Stored Pressure Type, UGTS Pressure Gauge , Gross Weight 13.3 Kg, Empty Weight 4.3 Kg, Can Height 575 mm, Diameter 180 ± 10mm, Discharge Time 31 Sec, Controllable discharge mechanism, Jet Range 6 Meters, Average Discharge is 90%, applicable on Class A,B & C and electrically started Fire, A Rating- 4A, B Rating 89B , Can Construction : Deep drawn & CO2 Mig welded, CE Marked Valve with inbuilt NRV & Safety Release Provision , EPDM Rubber Hose with both end Aluminum clamped , Plastic base provided, Internal Coating - Epoxy Powder coating, External Coating - Pure Polyester Powder coating (UV Resistant) , Brass forged valves with safety Pin is of SS material, and Welding Procedure approved by TPI with 6 G certification , Sheet metal thickness : 2.0 mm, Helium Leak Detection Tested, ISI Approved IS 15683:2006 and CE Certified , 5 Years Warranty.
--	-----------	--------------------------	--