



Product Short description for Enquiry RQ Series BC Dry Powder SBC Cartridge operated Fire Extinguishers

BC DRY POWDER SBC (CARTRIDGE OPERATED) 4 KG 21B FIRE EXTINGUISHER IS:15683

RQ	KFD-4	"KANEX" DCP type Fire extinguisher cap. 4 Kg. filled with SBC powder confirms to IS 4308 Applicable classes of fire B & C, Gross Weight 7.3 Kg, empty Weight 3.3 Kg, Can Height 510mm, Diameter 140 ± 10mm, CO2 gas Cartridge of 120 gm confirms to IS 4947, Controllable discharge mechanism with EPDM Hose & Open Nozzle, Discharge Time 15 Sec, Jet Range 4 Meters, Average Discharge is 90%, Fire rating: B Rating 21B , Can Construction : Deep drawn & MIG Welding technology, CE Marked Brass forged Squeeze grip type valves with Auto safety release at 24 bar (About 950 gm. wt.) and safety Pin is of SS material, Internal Coating - Epoxy Powder coating, External Coating - Pure Polyester Powder coating (UV Resistant) , Sheet metal thickness : 1.8 mm, Confirms to IS 15683:2006 and ISI Marked.
----	-------	-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------

BC DRY POWDER SBC (CARTRIDGE OPERATED) 6 KG 34B FIRE EXTINGUISHER IS:15683

RQ	KFD-6	"KANEX" DCP type Fire extinguisher cap. 6 Kg. filled with SBC powder confirms to IS 4308 Applicable classes of fire B & C, Gross Weight 10.3 Kg, empty Weight 4.3 Kg, Can Height 540mm, Diameter 150 ± 10mm, CO2 gas Cartridge of 120 gm confirms to IS 4947, Controllable discharge mechanism with EPDM Hose & Open Nozzle, Discharge Time 20 Sec, Jet Range 4.5 Meters, Average Discharge is 90%, Fire rating: B Rating 34B , Can Construction : Deep drawn & MIG Welding technology, CE Marked Brass forged Squeeze grip type valves with Auto safety release at 24 bar (About 950 gm. wt.) and safety Pin is of SS material, Internal Coating - Epoxy Powder coating, External Coating - Pure Polyester Powder coating (UV Resistant) , Sheet metal thickness : 1.8 mm, Confirms to IS 15683:2006 and ISI Marked.
----	-------	----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------

BC DRY POWDER SBC (CARTRIDGE OPERATED) 9 KG 34B FIRE EXTINGUISHER IS:15683

RQ	KFD-9	"KANEX" DCP type Fire extinguisher cap. 9 Kg. filled with SBC powder confirms to IS 4308 Applicable classes of fire B & C, Gross Weight 15.3 Kg, empty Weight 6.3 Kg, Can Height 540mm, Diameter 150 ± 10mm, CO2 gas Cartridge of 200 gm confirms to IS 4947, Controllable discharge mechanism with EPDM Hose & Open Nozzle, Discharge Time 30 Sec, Jet Range 5 Meters, Average Discharge is 90%, Fire rating: B Rating 34B , Can Construction : Deep drawn & MIG Welding technology, CE Marked Brass forged Squeeze grip type valves with Auto safety release at 24 bar (About 950 gm. wt.) and safety Pin is of SS material, Internal Coating - Epoxy Powder coating, External Coating - Pure Polyester Powder coating . Sheet metal thickness : 2.0 mm, Confirms to IS 15683:2006 and ISI Marked.
----	-------	-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------



Product Short description for Enquiry RQ Series BC Dry Powder SBC Cartridge operated Fire Extinguishers

BC DRY POWDER PBC (CARTRIDGE OPERATED) 4 KG 21B FIRE EXTINGUISHER IS:15683

RQ	KFD-4-P	"KANEX" DCP type Fire extinguisher cap. 4 Kg. filled with Potassium Bi carbonate based (PBC) powder confirms to IS 4308 Applicable classes of fire B & C, Gross Weight 7.3 Kg, empty Weight 3.3 Kg, Can Height 510mm, Diameter 140 ± 10mm, CO2 gas Cartridge of 120 gm, Controllable discharge mechanism with EPDM Hose & Open Nozzle, Discharge Time 15 Sec, Jet Range 4 Meters, Average Discharge is 90%, Fire rating: B Rating 21B , Can Construction : Deep drawn & MIG Welding technology, CE Marked Brass forged Squeeze grip type valves with Auto safety release at 24 bar (About 950 gm. wt.) and safety Pin is of SS material, Internal Coating - Epoxy Powder coating, External Coating - Pure Polyester Powder coating (UV Resistant) and Welding Procedure approved by TPI with 6 G certification . Sheet metal thickness: 1.8 mm, Confirms to IS 15683:2006 and ISI Marked, 5 Years Warranty.
----	---------	-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------

BC DRY POWDER PBC (CARTRIDGE OPERATED) 6 KG 34B FIRE EXTINGUISHER IS:15683

RQ	KFD-6-P	"KANEX" DCP type Fire extinguisher cap. 6 Kg. filled with Potassium Bi carbonate based (PBC) powder confirms to IS 4308 Applicable classes of fire B & C, Gross Weight 10.3 Kg, empty Weight 4.3 Kg, Can Height 540mm, Diameter 150 ± 10mm, CO2 gas Cartridge of 120 gm confirms to IS 4947, Controllable discharge mechanism with EPDM Hose & Open Nozzle, Discharge Time 20 Sec, Jet Range 4.5 Meters, Average Discharge is 90%, Fire rating: B Rating 34B , Can Construction : Deep drawn & MIG Welding technology, CE Marked Brass forged Squeeze grip type valves with Auto safety release at 24 bar (About 950 gm. wt.) and safety Pin is of SS material, Internal Coating - Epoxy Powder coating, External Coating - Pure Polyester Powder coating (UV Resistant) and Welding Procedure approved by TPI with 6 G certification . Sheet metal thickness : 1.8 mm, Confirms to IS 15683:2006 and ISI Marked, 5 Years Warranty.
----	---------	-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------

BC DRY POWDER PBC (CARTRIDGE OPERATED) 9 KG 34B FIRE EXTINGUISHER IS:15683

RQ	KFD-9-P	"KANEX" DCP type Fire extinguisher cap. 9 Kg. filled with Potassium Bi carbonate based (PBC) powder confirms to IS 4308 Applicable classes of fire B & C, Gross Weight 15.3 Kg, empty Weight 6.3 Kg, Can Height 585mm, Diameter 180 ± 10mm, CO2 gas Cartridge of 200 gm confirms to IS 4947, Controllable discharge mechanism with EPDM Hose & Open Nozzle, Discharge Time 30 Sec, Jet Range 5 Meters, Average Discharge is 90%, Fire rating: B Rating 34B , Can Construction : Deep drawn & MIG Welding technology, CE Marked Brass forged Squeeze grip type valves with Auto safety release at 24 bar (About 950 gm. wt.) and safety Pin is of SS material, Internal Coating - Epoxy Powder coating, External Coating - Pure Polyester Powder coating (UV Resistant) and Welding Procedure approved by TPI with 6 G certification . Sheet metal thickness : 2.0 mm, Confirms to IS 15683:2006 and ISI Marked, 5 Years Warranty.
----	---------	-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------