

DCP TROLLEY MOUNTED

Highly mobile, these units permit a single operator quick access to extinguishing of fires that would normally require several operators with large hand portables.



| MODEL (SBC) | KFD 25 | KFD 50 | KFD 75 |
|--|------------------|-------------|-------------|
| MODEL (MAP) | KFDA 25 | KFDA 50 | KFDA 75 |
| Capacity | 25 kg | 50 kg | 75 kg. |
| Design | Hose & Nozzle | | |
| Height (Approx.) | 980 mm. | 1020 mm. | 1030 mm. |
| Diameter (Approx.) | 300 ±10 mm. | 400 ±10 mm. | 400 ±10 mm. |
| Average Discharge time | 25 -30 Sec. | 40-50 Sec. | 50-60 Sec. |
| Average Range of throw | 6 m. | 8 m. | 10 m. |
| Minimum % Discharge | 85% | 85% | 85% |
| Operating Temperature | -30 °C to +55 °C | | |
| Service Pressure (Ps)/ Expansion Space | 14 kg/cm2. | | |
| Test Pressure | 30 kg/cm2. | | |
| Expelling Agent | CO2 Gas. | | |
| CO2 Gas Cylinder | 1 kg. | 2 kg. | 2 kg. |
| Full Weight (Approx.) | 64 kg. | 107 kg. | 146 kg. |
| Empty Weight (Approx.) | 39 kg. | 57 kg. | 73 kg. |
| Shipping Weight (Approx.) | 65 kg. | 110 kg. | 148 kg. |
| Packing Standard | Jute Bags | | |
| Approvals | BIS & CE | | |

MECHANICAL FOAM & WATER TYPE TROLLEY MOUNTED

Features a combination of mobility, 1-person operation & fire-killing power. KANEX Units utilize a regulator to maintain a consistent operating pressure and flow throughout the total extinguisher discharge.

| MODEL | KFM 50 | KFM 150 | KFW 50 | KFW 150 |
|----------------------------|-----------------------------|--------------|---------------|--------------|
| Capacity | 50 Ltr. | 150 Ltr. | 50 Ltr. | 150 Ltr. |
| Design | Hose & Air aspirated Nozzle | | Hose & Nozzle | |
| Height (Approx.) | 1285 mm. | 1350 mm. | 1285 mm. | 1350 mm. |
| Diameter (Approx.) | 300 ±10 mm. | 480 ±10 mm. | 300 ±10 mm. | 480 ±10 mm. |
| Average Discharge time | 40 -180 Sec. | 40 -180 Sec. | 40 -180 Sec. | 40 -180 Sec. |
| Average Range of throw | 10 m. | 10 m. | 10 m. | 10 m. |
| Minimum % Discharge | 90% | 90% | 90% | 90% |
| Operating Temperature | +5 °C to +55 °C | | | |
| Expansion Space (Ps) | 14 kg/cm2. | | | |
| Test Pressure | 30 kg/cm2. | | | |
| Expelling Agent | CO2 Gas. | | | |
| CO2 Gas Cartridge/Cylinder | 300 gm. | 2 kg. | 300 gm. | 2 kg. |
| Full Weight (Approx.) | 87 kg. | 249 kg. | 87 kg. | 249 kg. |
| Empty Weight (Approx.) | 37 kg. | 99 kg. | 37 kg. | 99 kg. |
| Shipping Weight (Approx.) | 89 kg. | 251 kg. | 89 kg. | 251 kg. |
| Packing Standard | Jute Bags | | | |
| Approvals | BIS & CE | -- | -- | -- |

CO₂ TYPE TROLLEY MOUNTED

KANEX CO₂ GAS extinguishers are characterized by their high performance for fires involving an electrical rick like computers, office equipment and generators etc. CO₂ is non-conductive, clean and safe, ensuring minimal damage to electrical equipment and furnishings.

| MODEL | KFC 6.5 | KFC 9 | KFC 22.5 |
|---------------------------|------------------|--------------|------------------|
| Capacity | 6.5 kg. | 9 kg. | 22.5 kg. |
| Design | Hose & Horn | Hose & Horn | Hose & Horn |
| Height (Approx.) | 960 mm. | 1250 mm. | 1155 mm. |
| Diameter (Approx.) | 140 ±10 mm. | 140 ±10 mm. | 232 ±10 mm. |
| Average Discharge time | 10 -20 Sec. | 15 -36 Sec. | 20 -60 Sec. |
| Average Range of throw | 10 m. | 10 m. | 10 m. |
| Minimum % Discharge | 95% | 95% | 95% |
| Operating Temperature | -30 °C to +55 °C | | |
| Service Pressure (Ps) | 60 bar. | | |
| Test Pressure | 250 bar. | | |
| Full Weight (Approx.) | 21 or 23 kg. | 29 or 32 kg. | 66 or 69 kg. |
| Empty Weight (Approx.) | 14.5 or 16.5 kg. | 20 or 23 kg. | 43.5 or 46.5 kg. |
| Shipping Weight (Approx.) | 22 or 24 kg. | 30 or 33 kg. | 67 or 70 kg. |
| Packing Standard | Jute Bags | | |
| Approvals | BIS & CE | | |