



Product Short description for Enquiry
RQ Series CO2 High Pressure trolley mounted Fire Extinguisher

CO2 (HIGH PRESSURE) 6.5 KG FIRE EXTINGUISHER

RQ	KFC-6.5	KANEX 6.5 kg CO2 High Pressure trolley mounted Fire Extinguisher , filled with Co2 Gas as per IS 15222, Gross Weight 21 Kg, empty weight 14.5 Kg, Control discharge mechanism fitted with 1 Meter Wire Braided Hose & Flat Horn with Diffuser Nozzle for dispersed discharge of CO2 , Discharge Time 20 Sec, Average Discharge is 95%, applicable on Class B, C and electrically started Fire, Internal coating is not applicable & External coating is of enamel spray painting, Valve Confirm to IS 3224 ISI Marked , CO2 Cylinder construction: hot spinning by seamless pipes & bearing ISI mark, Body confirms to IS 7285 and PESO APPROVED, Extinguishers confirmed to IS 2878:2004 and ISI maked.
-----------	----------------	--

CO2 (HIGH PRESSURE) 9 KG FIRE EXTINGUISHER

RQ	KFC-9	KANEX 9 kg CO2 High Pressure trolley mounted Fire Extinguisher , filled with Co2 Gas as per IS 15222, Gross Weight 29 Kg, empty weight 20 Kg, Control discharge mechanism fitted with 2 Meter Wire Braided Hose & Flat Horn with Diffuser Nozzle for dispersed discharge of CO2 , Discharge Time 30 Sec, Average Discharge is 95%, applicable on Class B, C and electrically started Fire, Internal coating is not applicable & External coating is of enamel spray painting, Valve Confirm to IS 3224 ISI Marked , CO2 Cylinder construction: hot spinning by seamless pipes & bearing ISI mark, Body confirms to IS 7285 and PESO APPROVED, Extinguishers confirmed to IS 2878:2004 and ISI maked. 5 Years Warranty.
-----------	--------------	--

CO2 (HIGH PRESSURE) 22.5 KG FIRE EXTINGUISHER

RQ	KFC-22.5	KANEX 22.5 kg CO2 High Pressure trolley mounted Fire Extinguisher , filled with Co2 Gas as per IS 15222, Gross Weight 66 Kg, empty weight 43.5 Kg, Control discharge mechanism fitted with 5 Meter Wire Braided Hose & Flat Horn with Diffuser Nozzle for dispersed discharge of CO2 , Discharge Time 50 Sec, Average Discharge is 95%, applicable on Class B, C and electrically started Fire, Internal coating is not applicable & External coating is of enamel spray painting, Valve Confirm to IS 3224 ISI Marked , CO2 Cylinder construction: hot spinning by seamless pipes & bearing ISI mark, Body confirms to IS 7285 and PESO APPROVED, Extinguishers confirmed to IS 2878:2004 and ISI maked.
-----------	-----------------	---