

## CO2 FIRE EXTINGUISHERS

### PERFORMANCE DATA

<b>MODEL</b>	<b>KFC 2</b>	<b>KFC 3</b>	<b>KFC 4.5</b>
Capacity	2 kg	3 kg	4.5 kg
Design	Hose & Nozzle		
Fire Rating	8B	13B	21B
Height (Approx.)	580 mm.	545 mm.	700 mm.
Diameter (Approx.)	108 ±10 mm.	140 ±10 mm.	140 ±10 mm.
Average Discharge time	9 Sec.	11 Sec.	12 Sec.
Average Range of throw	2.5 m.	2.5 m.	2.5 m.
Average % Discharge	96%	97%	96%
Operating Temperature	-30 °C to +55 °C		
Service Pressure (Ps)	60 bar.		
Max. Service Pressure (Pms)	106 bar.	110 bar.	105 bar.
Test Pressure	250 bar.		
Full Weight (Approx.)	8.9 or 8.2 kg.	12.5 or 11.4 kg.	17 or 16.4 kg.
Empty Weight (Approx.)	6.9 or 6.2 kg.	9.5 or 8.4 kg.	12.5 or 11.9 kg.
Shipping Weight (Approx.)	9 or 8.3 kg.	12.8 or 11.7 kg.	17.4 or 16.8 kg.
Packing Standard	Gunny Bags		
Mounting Bracket	Wall Bracket		
Approvals	BIS & CE (on request)		

### Fire Rating as per IS 15683:2006

<b>MODEL</b>	<b>A</b>	<b>B</b>	<b>Factory Tested</b>
KFC 2	NA	8B	13B
KFC 3	NA	13B	21B
KFC 4.5	NA	21B	34B