



Product Short description for Enquiry RQ Series High Pressure Portable CO2 Fire Extinguishers

CO2 (HIGH PRESSURE) 2 KG 8B FIRE EXTINGUISHER

| | | |
|----|-------|---|
| RQ | KFC-2 | KANEX 2 kg CO2 High Pressure portable Fire Extinguisher , filled with CO2 Gas as per IS 15222, Gross Weight 8.2, empty weight 6.2 Kg, Control discharge mechanism fitted with Bend pipe and Discharge Horn, Discharge Time 9 Sec, Average Discharge is 95%, Applicable on Class B, C and electrically started Fire, Fire Rating 8B , Internal coating is not applicable & External coating is of enamel spray painting, Powder Coated Handle, Valve Confirm to IS 3224 ISI Marked , bearing ISI mark. CO2 Cylinder construction: hot spinning by seamless pipes & bearing ISI mark, Body confirms to IS 7285 and PESO APPROVED, Extinguishers confirmed to IS 15683:2006 and ISI maked. |
|----|-------|---|

CO2 (HIGH PRESSURE) 3 KG 13B FIRE EXTINGUISHER

| | | |
|----|-------|--|
| RQ | KFC-3 | KANEX 3 kg CO2 High Pressure Portable Fire Extinguisher , filled with Co2 Gas as per IS 15222, Gross Weight 11.4, empty weight 8.4 Kg, Control discharge mechanism fitted with Bend pipe and Discharge Horn, Discharge Time 11 Sec, Average Discharge is 95%, Applicable on Class B, C and electrically started Fire, Fire Rating 13B , Internal coating is not applicable & External coating is of enamel spray painting, Powder Coated Handle, Valve Confirm to IS 3224 ISI Marked , bearing ISI mark. CO2 Cylinder construction: hot spinning by seamless pipes & bearing ISI mark, Body confirms to IS 7285 and PESO APPROVED, Extinguishers confirmed to IS 15683:2006 and ISI maked. |
|----|-------|--|

CO2 (HIGH PRESSURE) 4.5 KG 21B FIRE EXTINGUISHER

| | | |
|----|---------|--|
| RQ | KFC-4.5 | KANEX 4.5 kg CO2 High Pressure Portable Fire Extinguisher , filled with Co2 Gas as per IS 15222, Gross Weight 16.4, empty weight 11.9 Kg, Control discharge mechanism fitted with 1 Meter Wire Braided Hose & Flat Horn with Diffuser Nozzle for dispersed discharge of CO2 , Discharge Time 12 Sec, Average Discharge is 95%, Applicable on Class B, C and electrically started Fire, Fire Rating 21B , Internal coating is not applicable & External coating is of enamel spray painting, Powder Coated Handle, Valve Confirm to IS 3224 ISI Marked , CO2 Cylinder construction: hot spinning by seamless pipes & bearing ISI mark, Body confirms to IS 7285 and PESO APPROVED, Extinguishers confirmed to IS 15683:2006 and ISI maked. |
|----|---------|--|