

DCP FIRE EXTINGUISHERS			
PERFORMANCE DATA			
MODEL (SBC)	KFD 4	KFD 6	KFD 9
MODEL (MAP)	KFDA 4	KFDA 6	KFDA 9
Capacity	4 kg	6 kg	9 kg.
Design	Hose & Nozzle		
Fire Rating (Regular SBC)	21B	34B	34B
Fire Rating (MAP)	2A : 34B	3A : 55B	4A : 89B
Height (Approx.)	510 mm.	540 mm.	585 mm.
Diameter (Approx.)	140±10 mm.	150±10 mm.	180±10 mm.
Average Discharge time	15 Sec.	20 Sec.	30 Sec.
Average Range of throw	4 m.	4.5 m.	5 m.
Average % Discharge	94%	94%	93%
Operating Temperature	-30 °C to +55 °C		
Service Pressure (Ps)	14 bar.		
Max. Service Pressure (Pms)	16 bar.		
Test Pressure	35 bar.		
Expelling Agent	CO2 Gas.		
CO2 Gas Cartridge	120 gm.	120 gm.	200 gm.
Full Weight (Approx.)	7.3 kg.	10.3 kg.	15.3 kg.
Empty Weight (Approx.)	3.3 kg.	4.3 kg.	6.3 kg.
Shipping Weight (Approx.)	7.5 kg.	10.5 kg.	15.7 kg.
Packing Standard	2 in 1- 21"X6.75"X14.10"	2 in 1- 22.5"X6.75"X14.10"	2 in 1- 24.75"X15.3"X8"
Mounting Bracket	Wall Barcket		
Approvals	BIS & CE (on request)		
* Indicates factory tested			

Fire Rating as per IS 15683:2006 (Regular SBC)		
MODEL	A	B
KFD 4	NA	21B
KFD 6	NA	34B
KFD 9	NA	34B
Fire Rating as per IS 15683:2006 (With MAP Powder)		
KFDA 4	2A	34B
KFDA 6	3A	55B
KFDA 9	4A	89B