



Product Short description for Enquiry HQ Series F Class Kitchen Fire Extinguishers

F CLASS KITCHEN (STORED PRESSURE) 2 LTR. FIRE EXTINGUISHER

HQ	KFK2	"KANEX" 2 ltr. Fire Extinguisher K Class Kitchen Wet chemical (Blend of Potassium Acetate, Potassium citrate or Potassium carbonate), Smooth and Polished Stainless Steel body, Applicable fire class K, UGTS Pressure Gauge, Gross Weight 3.7 Kg, empty Weight 1.7 Kg, Height 440mm, Diameter 110 ± 10mm, Discharge Time 12 Sec, Controllable discharge mechanism, Jet Range 3 Meters, Average Discharge is 96%, EPDM Hose & Specially designed Nozzle that allows a broad, dispersed discharge of agent that delivers a high volume, low velocity delivery of wet chemical which doesnt cause the cooking oil to splash. CE Marked Valve with inbuilt NRV & Safety Release Provision and safety Pin is of SS material, Sheet metal thickness : 0.9 to 1 mm. CE Marked.
----	------	---

K CLASS KITCHEN (STORED PRESSURE) 3 LTR. FIRE EXTINGUISHER

HQ	KFK3	"KANEX" 3 ltr. Fire Extinguisher K Class Kitchen Wet chemical (Blend of Potassium Acetate, Potassium citrate or Potassium carbonate), Smooth and Polished Stainless Steel body, Applicable fire class K, UGTS Pressure Gauge, Gross Weight 5.3 Kg, empty Weight 2.3 Kg, Can Height 500mm, Diameter 140 ± 10mm, Discharge Time 14 Sec, Controllable discharge mechanism, Jet Range 3.5 Meters, Average Discharge is 97%, Controllable discharge mechanism with EPDM Hose & Specially designed Nozzle that allows a broad, dispersed discharge of agent that delivers a high volume, low velocity delivery of wet chemical which doesnt cause the cooking oil to splash. CE Marked Valve with inbuilt NRV & Safety Release Provision and safety Pin is of SS material, Sheet metal thickness : 0.9 to 1 mm. CE Marked.
----	------	---

K CLASS KITCHEN (STORED PRESSURE) 6 LTR. FIRE EXTINGUISHER

HQ	KFK6	"KANEX" 6 ltr. Fire Extinguisher K Class Kitchen Wet chemical (Blend of Potassium Acetate, Potassium citrate or Potassium carbonate), Smooth and Polished Stainless Steel body, Applicable fire class K, UGTS Pressure Gauge, Can Height 550 mm, Diameter 150 ± 10mm, Discharge Time 13 Sec, Jet Range 2 Meters, Average Discharge is 90%, Controllable discharge mechanism with EPDM Hose & Specially designed Nozzle that allows a broad, dispersed discharge of agent that delivers a high volume, low velocity delivery of wet chemical which doesnt cause the cooking oil to splash. CE Marked Valve with inbuilt NRV & Safety Release Provision and safety Pin is of SS material, Sheet metal thickness : 0.9 to 1 mm. CE Marked.
----	------	--

K CLASS KITCHEN (STORED PRESSURE) 9 LTR. FIRE EXTINGUISHER

HQ	KFK9	"KANEX" 9 ltr. Fire Extinguisher K Class Kitchen Wet chemical (Blend of Potassium Acetate, Potassium citrate or Potassium carbonate), Smooth and Polished Stainless Steel body, Applicable fire class K, UGTS Pressure Gauge, Can Height 620 mm, Diameter 180 ± 10mm, Discharge Time 13 Sec, Jet Range 2 Meters, Average Discharge is 90%, Controllable discharge mechanism with EPDM Hose & Specially designed Nozzle that allows a broad, dispersed discharge of agent that delivers a high volume, low velocity delivery of wet chemical which doesnt cause the cooking oil to splash, CE Marked Valve with inbuilt NRV & Safety Release Provision and safety Pin is of SS material, Sheet metal thickness : 0.9 to 1 mm. CE Marked.
----	------	--