



## Product Short description for Enquiry RQ & HQ Series Mechanical Foam Cartridge operated Fire Extinguishers

### MECHANICAL FOAM (CARTRIDGE OPERATED) 6 LTR. FIRE EXTINGUISHER

RQ	KFMC-6	<b>KANEX 6 ltr. Mechanical Foam Cartridge type Fire Extinguishers filled with AFFF Foam confirms to IS 4989 (Part-II).</b> Applicable fire class A & B, Gross Weight 9 Kg, empty Weight 3.9 Kg, Can Height 530 mm, Diameter 150 ± 10mm, Controllable discharge mechanism, Discharge Time 21 Sec, Jet Range 5 Meters, Average Discharge is 95%, <b>Tested Fire Rating-1A:21B</b> , Can Construction : Deep drawn & CO2 Mig welded, Controllable discharge mechanism with <b>EPDM Hose &amp; Air aspirated Nozzle</b> , CO2 gas Cartridge of 60 gm Confirms to IS 4947, <b>External Pure polyester powder coated and Internal Plastic lining, CE Marked Valve with Safety Release Provision and</b> safety Pin is of SS material, Sheet metal thickness : 1.8 mm, Construction as IS 15683:2006, <b>CE Marked.</b>
----	--------	--

### MECHANICAL FOAM (CARTRIDGE OPERATED) 9 LTR. FIRE EXTINGUISHER

RQ	KFMC-9	<b>KANEX 9 ltr. Mechanical Foam Cartridge type Fire Extinguishers filled with AFFF Foam confirms to IS 4989 (Part-II).</b> Applicable fire class A & B, Applicable fire class A, Gross Weight 13 Kg, empty weight 5.3 Kg, Can Height 585mm, Diameter 180 ± 10mm, Controllable discharge mechanism, Discharge Time 35 Sec, Jet Range 7 Meters, Average Discharge is 95%, <b>Fire Rating- 4A &amp; 34B</b> , Can Construction : Deep drawn & CO2 Mig welded, <b>CE Marked Valve with Safety Release Provision</b> , Controllable discharge mechanism with <b>EPDM Hose &amp; Air aspirated Nozzle</b> , CO2 gas Cartridge of 60 gm. Confirms to IS 4947, <b>External Pure polyester powder coated (UV Resistant) and Internal Plastic lining</b> , Sheet metal thickness : 2 mm, As per 15683:2006, ISI Marked.
----	--------	---

### MECHANICAL FOAM (CARTRIDGE OPERATED) 6 LTR. FIRE EXTINGUISHER

HQ	KFMC-6-AR	<b>KANEX 6 ltr. Mechanical Foam type Fire Extinguisher AR-AFFF Foam confirms to IS 4989 (Part-II)</b> , Applicable fire class A & B, Gross Weight 9 Kg, empty Weight 3.9 Kg, Can Height 530 mm, Diameter 150 ± 10mm, Controllable discharge mechanism, Discharge Time 21 Sec, Jet Range 5 Meters, Average Discharge is 95%, <b>Tested Fire Rating-1A:21B</b> , Can Construction : Deep drawn & CO2 Mig welded, Controllable discharge mechanism with <b>EPDM Hose &amp; Air aspirated Nozzle</b> , CO2 gas Cartridge of 60 gm Confirms to IS 4947, <b>External Pure polyester powder coated and Internal Plastic lining, CE Marked Valve with Safety Release Provision and</b> safety Pin is of SS material, Sheet metal thickness : 1.8 mm, Construction as IS 15683:2006, <b>CE Marked.</b>
----	-----------	---



**Product Short description for Enquiry**  
**RQ & HQ Series Mechanical Foam Cartridge operated Fire Extinguishers**

**MECHANICAL FOAM (CARTRIDGE OPERATED) 9 LTR. FIRE EXTINGUISHER**

<b>HQ</b>	<b>KFMC-9-AR</b>	<p><b>KANEX 9 ltr. Mechanical Foam type Fire Extinguisher AR-AFFF Foam confirms to IS 4989 (Part-II)</b>, Applicable fire class A &amp; B, Applicable fire class A, Gross Weight 13 Kg, empty weight 5.3 Kg, Can Height 585mm, Diameter 180 ± 10mm, Controllable discharge mechanism, Discharge Time 35 Sec, Jet Range 7 Meters, Average Discharge is 95%, <b>Fire Rating- 4A &amp; 34B</b>, Can Construction : Deep drawn &amp; CO2 Mig welded, <b>CE Marked Valve with Safety Release Provision</b>, Controllable discharge mechanism with <b>EPDM Hose &amp; Air aspirated Nozzle</b>, CO2 gas Cartridge of 60 gm. Confirms to IS 4947, <b>External Pure polyester powder coated (UV Resistant) and Internal Plastic lining</b>, Sheet metal thickness : 2 mm, As per 15683:2006, ISI Marked.</p>
-----------	------------------	--