



Product Short description for Enquiry HQ Series Mechanical Foam Stored Pressure(SS Body) Fire Extinguishers

MECHANICAL FOAM -SS (STORED PRESSURE) 6 LTR.

HQ	KFMSS6	KANEX 6 ltr. Mechanical Foam stored pressure type Fire Extinguisher filled with AR-AFFF Foam confirms to IS 4989 (Part-II). Smooth and polished stainless steel body , Applicable fire class A & B, UGTS Pressure Gauge, Gross Weight 8 Kg, empty Weight 2.9 Kg, Can Height 530 mm, Diameter 150 ± 10mm, Discharge Time 22 Sec, Controllable discharge mechanism, Jet Range 5 Meters, Average Discharge is 95%, Can Construction : Deep drawn & CO2 Mig welded, Controllable discharge mechanism with EPDM Hose & Air aspirated Nozzle, Internal Plastic lining, CE Marked Valve with inbuilt NRV & Safety Release Provision , safety Pin is of SS material, and Welding Procedure approved by TPI with 6 G certification. Sheet metal thickness : 1.8 mm, Construction as per IS 15683:2006, CE Marked . 1 Years Warranty
----	--------	---

MECHANICAL FOAM -SS (STORED PRESSURE) 9 LTR.

HQ	KFMSS9	KANEX 9 ltr. Mechanical Foam stored pressure type Fire Extinguisher filled with AR-AFFF Foam confirms to IS 4989 (Part-II). Smooth and polished stainless steel body , Applicable fire class A & B, UTGS Pressure Gauge, Gross Weight 12 Kg, empty weight 4.3 Kg, Can Height 630mm, Diameter 180 ± 10mm, Discharge Time 35 Sec, Controllable discharge mechanism, Jet Range 7 Meters, Average Discharge is 95%, Factory tested 4A:34B , Can Construction : Deep drawn & CO2 Mig welded, Controllable discharge mechanism with EPDM Hose & Air aspirated Nozzle, Internal Plastic lining, CE Marked Valve with inbuilt NRV & Safety Release Provision , Sheet metal thickness : 2 mm, Construction as per IS 15683:2006, ISI and CE Marked , 1 Years Warranty
----	--------	--