



FOAM & WATER TYPE STORED PRESSURE (SS BODY)

KANEX Stored Pressure Foam & Water extinguishers are ideal for fires involving volatile liquids and freely burning materials such as paper, cloth, wood and furniture.

Note : Mechanical Foam & Water extinguishers are not suitable for fires involving electrical risk.

• Water Type Suitable for Class A Fire Risk

• Foam Type Suitable for Class A and Class B Fire Risk



Class A



Class A



Class B



FEATURES

- ✓ Smooth & Polished Stainless Steel body.
- ✓ AFFF Aqueous Film Forming Foam Agent capable of fighting class A, B fire & Water capable of fighting class A fire
- ✓ CE Certified
- ✓ Smooth finish & also available with high quality PP powder coating
- ✓ Spray nozzle to provide high fire rating
- ✓ Choice of capacity 6 Ltrs. & 9 Ltrs.
- ✓ Controlled discharge
- ✓ Brass nickel plated head valve with simple squeeze operation
- ✓ Unique gauge testing system (UGTS)
- ✓ Rechargeable and easy to service
- ✓ High quality EPDM Rubber braided hose is far more flexible than the normal rubber used in hose pipe and also far less prone to cracks.

Ideal Use:

Petrol Stations, Restaurants, etc.

Caution :

Don't use on Electrical Fire.

Fire Rating as per IS 15683:2006

TYPE	MODEL	A	B
FOAM	KFM6-S	1A	13B
	KFM9-S	2A	21B
WATER	KFW6-S	2A	NA
	KFW9-S	3A	NA

PERFORMANCE DATA

TYPE	Mechanical Foam		Water CO ₂	
	KFMSS6-S	KFMSS9-S	KFWSS6-S	KFWSS9-S
Capacity	6 Ltr.	9 Ltr.	6 Ltr.	9 Ltr.
Design	Hose & Air aspirated Nozzle		Hose & Nozzle	
Fire Rating	1A:13B	2A:21B	2A	2A
Height (Approx.)	550 mm.	645 mm.	550 mm.	645 mm.
Diameter (Approx.)	162±10 mm.	180±10 mm.	162±10 mm.	180±10 mm.
Average Discharge time	22 Sec.	35 Sec.	22 Sec.	35 Sec.
Average Range of throw	5 m.	7 m.	5 m.	7 m.
Average % Discharge	98%	98%	99%	99%
Operating Temperature	+5 °C to +55 °C		+5 °C to +55 °C	
Service Pressure (Ps)	15 bar.		15 bar.	
Max. Service Pressure (Pms)	17 bar.		17 bar.	
Test Pressure	35 bar.		35 bar.	
Expelling Agent	Nitrogen (UHP Grade)		Nitrogen (UHP Grade)	
Full Weight (Approx.)	8 kg.	12 kg.	8 kg.	12 kg.
Empty Weight (Approx.)	2.9 kg.	4.3 kg.	2.9 kg.	4.3 kg.
Shipping Weight (Approx.)	8.2 kg.	12.3 kg.	8.2 kg.	12.3 kg.
Mounting Bracket	Wall bracket		Wall bracket	
Approvals	CE		CE	