



Product Short description for Enquiry
HQ Series Monnex Powder Stored Pressure Fire Extinguishers

		MONNEX DRY POWDER (STORED PRESSURE) 1 KG 89B FIRE EXTINGUISHER
HQ	KF MNX 1	KANEX Fire Extinguisher Cap. 1 kg Filled with Monnex Powder , Stored Pressure Type, UGTS Pressure Gauge , Gross Weight 3.4 Kg, Empty Weight 1.4 Kg, Can Height 380mm, Diameter 106 ± 10mm, Discharge Time 8 Sec, Controllable discharge mechanism, Jet Range 2 Meters, Average Discharge is 90%, applicable on Class A,B & C and electrically started Fire, B Rating 89B , Can Construction : Deep drawn & CO2 Mig welded, CE Marked Valve with inbuilt NRV & Safety Release Provision , Internal Coating - Epoxy Powder coating, External Coating - Pure Polyester Powder coating (UV Resistant) , Brass forged valves with safety Pin is of SS material, and Welding Procedure approved by TPI with 6 G certification , Sheet metal thickness : 1.6 mm, Helium Leak Detection Tested, ISI Approved IS 15683:2006 and CE Certified , 5 Years Warranty.
		MONNEX DRY POWDER (STORED PRESSURE) 2 KG 144B FIRE EXTINGUISHER
HQ	KF MNX 2	KANEX Fire Extinguisher Cap. 2 kg Filled with Monnex Powder , Stored Pressure Type, UGTS Pressure Gauge , Gross Weight 6.6 Kg, Empty Weight 2.6 Kg, Can Height 490mm, Diameter 140 ± 10mm, Discharge Time 18 Sec, Controllable discharge mechanism, Jet Range 3 Meters, Average Discharge is 90%, applicable on Class A,B & C and electrically started Fire, B Rating 144B , Can Construction : Deep drawn & CO2 Mig welded, CE Marked Valve with inbuilt NRV & Safety Release Provision , EPDM Rubber Hose with both end Aluminum clamped, Plastic base provided , Internal Coating - Epoxy Powder coating, External Coating - Pure Polyester Powder coating(UV Resistant) , Brass forged valves with safety Pin is of SS material, and Welding Procedure approved by TPI with 6 G certification , Sheet metal thickness : 1.8 mm, Helium Leak Detection Tested, ISI Approved IS 15683:2006 and CE Certified , 5 Years Warranty.



Product Short description for Enquiry
HQ Series Monnex Powder Stored Pressure Fire Extinguishers

		MONNEX DRY POWDER (STORED PRESSURE) 4 KG 183B FIRE EXTINGUISHER
HQ	KF MNX 4	KANEX Fire Extinguisher Cap. 6 kg Filled with Monnex Powder , Stored Pressure Type, UGTS Pressure Gauge , Gross Weight 8.9 Kg, Empty Weight 2.9 Kg, Can Height 530 mm, Diameter 150 ± 10mm, Discharge Time 24 Sec, Controllable discharge mechanism, Jet Range 5 Meters, Average Discharge is 90%, applicable on Class A,B & C and electrically started Fire, B Rating 183B , Can Construction : Deep drawn & CO2 Mig welded, CE Marked Valve with inbuilt NRV & Safety Release Provision , EPDM Rubber Hose with both end Aluminum clamped, Plastic base provided , Internal Coating - Epoxy Powder coating, External Coating - Pure Polyester Powder coating (UV Resistant) , Brass forged valves with safety Pin is of SS material, and Welding Procedure approved by TPI with 6 G certification , Sheet metal thickness : 1.8 mm, Helium Leak Detection Tested, ISI Approved IS 15683:2006 and CE Certified , 5 Years Warranty.
		MONNEX DRY POWDER (STORED PRESSURE) 9 KG 233B FIRE EXTINGUISHER
HQ	KF MNX 6	KANEX Fire Extinguisher Cap. 9 kg Filled with Monnex Powder , Stored Pressure Type, UGTS Pressure Gauge , Gross Weight 13.3 Kg, Empty Weight 4.3 Kg, Can Height 575 mm, Diameter 180 ± 10mm, Discharge Time 31 Sec, Controllable discharge mechanism, Jet Range 6 Meters, Average Discharge is 90%, applicable on Class A,B & C and electrically started Fire, B Rating 233B , Can Construction : Deep drawn & CO2 Mig welded, CE Marked Valve with inbuilt NRV & Safety Release Provision , EPDM Rubber Hose with both end Aluminum clamped, Plastic base provided , Internal Coating - Epoxy Powder coating, External Coating - Pure Polyester Powder coating (UV Resistant) , Brass forged valves with safety Pin is of SS material, and Welding Procedure approved by TPI with 6 G certification , Sheet metal thickness : 2.0 mm, Helium Leak Detection Tested, ISI Approved IS 15683:2006 and CE Certified , 5 Years Warranty.