

DCP TROLLEY MOUNTED

Highly mobile, these units permit a single operator quick access to extinguishing of fires that would normally require several operators with large hand portables.



MODEL (SBC)	KFD 25	KFD 50	KFD 75
MODEL (MAP)	KFDA 25	KFDA 50	KFDA 75
Capacity	25 kg	50 kg	75 kg.
Design	Hose & Nozzle		
Height (Approx.)	980 mm.	1020 mm.	1030 mm.
Diameter (Approx.)	300 ±10 mm.	400 ±10 mm.	400 ±10 mm.
Average Discharge time	25 -30 Sec.	40-50 Sec.	50-60 Sec.
Average Range of throw	6 m.	8 m.	10 m.
Minimum % Discharge	85%	85%	85%
Operating Temperature	-30 °C to +55 °C		
Service Pressure (Ps)/ Expansion Space	14 kg/cm2.		
Test Pressure	30 kg/cm2.		
Expelling Agent	CO2 Gas.		
CO2 Gas Cylinder	1 kg.	2 kg.	2 kg.
Full Weight (Approx.)	64 kg.	107 kg.	146 kg.
Empty Weight (Approx.)	39 kg.	57 kg.	73 kg.
Shipping Weight (Approx.)	65 kg.	110 kg.	148 kg.
Packing Standard	Jute Bags		
Approvals	BIS & CE		

MECHANICAL FOAM & WATER TYPE TROLLEY MOUNTED

Features a combination of mobility, 1-person operation & fire-killing power. KANEX Units utilize a regulator to maintain a consistent operating pressure and flow throughout the total extinguisher discharge.

MODEL	KFM 50	KFM 150	KFW 50	KFW 150
Capacity	50 Ltr.	150 Ltr.	50 Ltr.	150 Ltr.
Design	Hose & Air aspirated Nozzle		Hose & Nozzle	
Height (Approx.)	1285 mm.	1350 mm.	1285 mm.	1350 mm.
Diameter (Approx.)	300 ±10 mm.	480 ±10 mm.	300 ±10 mm.	480 ±10 mm.
Average Discharge time	40 -180 Sec.	40 -180 Sec.	40 -180 Sec.	40 -180 Sec.
Average Range of throw	10 m.	10 m.	10 m.	10 m.
Minimum % Discharge	90%	90%	90%	90%
Operating Temperature	+5 °C to +55 °C			
Expansion Space (Ps)	14 kg/cm2.			
Test Pressure	30 kg/cm2.			
Expelling Agent	CO2 Gas.			
CO2 Gas Cartridge/Cylinder	300 gm.	2 kg.	300 gm.	2 kg.
Full Weight (Approx.)	87 kg.	249 kg.	87 kg.	249 kg.
Empty Weight (Approx.)	37 kg.	99 kg.	37 kg.	99 kg.
Shipping Weight (Approx.)	89 kg.	251 kg.	89 kg.	251 kg.
Packing Standard	Jute Bags			
Approvals	BIS & CE	--	--	--

CO₂ TYPE TROLLEY MOUNTED

KANEX CO₂ GAS extinguishers are characterized by their high performance for fires involving an electrical rick like computers, office equipment and generators etc. CO₂ is non-conductive, clean and safe, ensuring minimal damage to electrical equipment and furnishings.

MODEL	KFC 6.5	KFC 9	KFC 22.5
Capacity	6.5 kg.	9 kg.	22.5 kg.
Design	Hose & Horn	Hose & Horn	Hose & Horn
Height (Approx.)	960 mm.	1250 mm.	1155 mm.
Diameter (Approx.)	140 ±10 mm.	140 ±10 mm.	232 ±10 mm.
Average Discharge time	10 -20 Sec.	15 -36 Sec.	20 -60 Sec.
Average Range of throw	10 m.	10 m.	10 m.
Minimum % Discharge	95%	95%	95%
Operating Temperature	-30 °C to +55 °C		
Service Pressure (Ps)	60 bar.		
Test Pressure	250 bar.		
Full Weight (Approx.)	21 or 23 kg.	29 or 32 kg.	66 or 69 kg.
Empty Weight (Approx.)	14.5 or 16.5 kg.	20 or 23 kg.	43.5 or 46.5 kg.
Shipping Weight (Approx.)	22 or 24 kg.	30 or 33 kg.	67 or 70 kg.
Packing Standard	Jute Bags		
Approvals	BIS & CE		