

DCP TROLLEY MOUNTED FIRE EXTINGUISHERS			
PERFORMANCE DATA			
MODEL (SBC)	KFD 25	KFD 50	KFD 75
MODEL (MAP)	KFDA 25	KFDA 50	KFDA 75
Capacity	25 kg	50 kg	75 kg.
Design	Hose & Nozzle		
Height (Approx.)	980 mm.	1020 mm.	1030 mm.
Diameter (Approx.)	300 ±10 mm.	400 ±10 mm.	400 ±10 mm.
Average Discharge time	25 -30 Sec.	40-50 Sec.	50-60 Sec.
Average Range of throw	6 m.	8 m.	10 m.
Minimum % Discharge	85%	85%	85%
Operating Temperature	-30 °C to +55 °C		
Service Pressure (Ps)/ Expansion Space	14 kg/cm2.		
Test Pressure	30 kg/cm2.		
Expelling Agent	CO2 Gas.		
CO2 Gas Cylinder	1 kg.	2 kg.	2 kg.
Full Weight (Approx.)	64 kg.	107 kg.	146 kg.
Empty Weight (Approx.)	39 kg.	57 kg.	73 kg.
Shipping Weight (Approx.)	65 kg.	110 kg.	148 kg.
Packing Standard	Jute Bags		
Approvals	BIS & CE (on request)		