

MECHANICAL FOAM TROLLEY MOUNTED FIRE EXTINGUISHERS

PERFORMANCE DATA

MODEL	KFM 50	KFM 150	KFW 50	KFW 150
Capacity	50 Ltr.	150 Ltr.	50 Ltr.	150 Ltr.
Design	Hose & Air aspirated Nozzle	Hose & Air aspirated Nozzle	Hose & Nozzle	Hose & Nozzle
Height (Approx.)	1285 mm.	1350 mm.	1285 mm.	1350 mm.
Diameter (Approx.)	300 ±10 mm.	480 ±10 mm.	300 ±10 mm.	480 ±10 mm.
Average Discharge time	40 -180 Sec.	40 -180 Sec.	40 -180 Sec.	40 -180 Sec.
Average Range of throw	10 m.	10 m.	10 m.	10 m.
Minimum % Discharge	90%	90%	90%	90%
Operating Temperature	+5 °C to +55 °C			
Expansion Space (Ps)	14 kg/cm ² .			
Test Pressure	30 kg/cm ² .			
Expelling Agent	CO ₂ Gas.			
CO ₂ Gas Cartridge/Cylinder	300 gm.	2 kg.	300 gm.	2 kg.
Full Weight (Approx.)	87 kg.	249 kg.	87 kg.	249 kg.
Empty Weight (Approx.)	37 kg.	99 kg.	37 kg.	99 kg.
Shipping Weight (Approx.)	89 kg.	251 kg.	89 kg.	251 kg.
Packing Standard	Jute Bags			
Approvals	BIS & CE (on request)	--	--	--