



Product Short description for Enquiry RQ Series Water Cartridge Operated Fire Extinguishers

WATER (CARTRIDGE OPERATED) 6 LTR. FIRE EXTINGUISHER

RQ	KFW6-C	KANEX 6 ltr. Water type cartridge operated Fire Extinguisher. Applicable fire class A, Gross Weight 9 Kg, empty Weight 3.9 Kg, Can Height 530 mm, Diameter 150 ± 10mm, Controllable discharge mechanism, Discharge Time 21 Sec, Jet Range 5 Meters, Average Discharge is 95%, Fire Rating- 2A , Can Construction : Deep drawn & CO2 Mig welded, CE Marked Valve with inbuilt NRV & Safety Release Provision , Controllable discharge mechanism with EPDM Hose & Nozzle , CO2 gas Cartridge of 60 gm (Confirms to IS 4947), External Pure polyester powder coated (UV Resistant) and Internal Plastic lining , Brass forged valves with safety Pin is of SS material, Sheet metal thickness : 1.8 mm, Construction as IS 15683:2006, CE Marked .
-----------	---------------	---

WATER (CARTRIDGE OPERATED) 9 LTR. 3A FIRE EXTINGUISHER

RQ	KFW9-C	KANEX 9 ltr. Fire Extinguisher Water type cartridge operated. Applicable fire class A, UTGS Pressure Gauge , Gross Weight 13 Kg, empty weight 5.3 Kg, Can Height 585mm, Diameter 180 ± 10mm, Discharge Time 35 Sec, Controllable discharge mechanism, Jet Range 7 Meters, Average Discharge is 95%, Fire Rating- 3A , Can Construction : Deep drawn & CO2 Mig welded, CE Marked Valve with inbuilt NRV & Safety Release Provision , Controllable discharge mechanism with EPDM Hose & Nozzle , CO2 gas Cartridge of 60 gm. Internal Plastic Lining and External Coating - Pure Polyester Powder coating (UV Resistant) , Sheet metal thickness : 2 mm, Construction as per IS 15683:2006 and ISI Marked, 1 Years Warranty.
-----------	---------------	--