



## Product Short description for Enquiry HQ Series Water Stored Pressure(SS Body) Fire Extinguishers

### WATER (STORED PRESSURE) 6 LTR. (SS) FIRE EXTINGUISHER

<b>HQ</b>	<b>KFW6-SS</b>	<b>KANEX 6 ltr. Water type stored pressure Fire Extinguisher filled with water of TDS 3 to 4 PPM, Smooth and polished stainless steel body</b> , Applicable fire class A, <b>UGTS Pressure Gauge</b> , Gross Weight 8 Kg, empty Weight 2.9 Kg, Can Height 530 mm, Diameter 150 ± 10mm, Discharge Time 22 Sec, Controllable discharge mechanism, Jet Range 5 Meters, Average Discharge is 95%, Factory tested <b>Fire Rating- 2A</b> , Can Construction : Deep drawn & CO2 Mig welded, Controllable discharge mechanism with <b>EPDM Hose &amp; Nozzle, CE Marked Valve with inbuilt NRV &amp; Safety Release Provision</b> , safety Pin is of SS material, and Welding Procedure approved by TPI with 6 G certification. Sheet metal thickness: 1.8 mm, Construction as per IS 15683:2006, <b>CE Marked</b> . 1 year Warranty.
-----------	----------------	--

### WATER (STORED PRESSURE) 9 LTR. (S) FIRE EXTINGUISHER

<b>HQ</b>	<b>KFW9-SS</b>	<b>KANEX 9 ltr. Water type stored pressure Fire Extinguisher filled with water of TDS 3 to 4 PPM, Smooth and polished stainless steel body</b> , Applicable fire class A, <b>UTGS Pressure Gauge</b> , Gross Weight 12 Kg, empty weight 4.3 Kg, Can Height 575mm, Diameter 180 ± 10mm, Discharge Time 35 Sec, Controllable discharge mechanism, Jet Range 7 Meters, Average Discharge is 95%, applicable on Class A, Factory tested <b>Fire Rating- 4A</b> , Can Construction : Deep drawn & CO2 Mig welded, <b>CE Marked Valve with inbuilt NRV &amp; Safety Release Provision</b> , safety Pin is of SS material,, Controllable discharge mechanism with <b>EPDM Hose &amp; Nozzle, Internal Coating – Plastic Lining</b> , Sheet metal thickness : 2mm, construction as per IS 15683:2006, <b>ISI and CE Marked</b> , 1 Years Warranty
-----------	----------------	---