

## FOAM STORED PRESSURE FIRE EXTINGUISHER

### PERFORMANCE DATA

MODEL	KFM6-S	KFM9-S
Capacity	6 Ltr.	9 Ltr.
Design	Hose & Air aspirated Nozzle	
Fire Rating	1A:13B	2A:21B
Height (Approx.)	530 mm.	575 mm.
Diameter (Approx.)	150±10 mm.	180±10 mm.
Average Discharge time	22 Sec.	35 Sec.
Average Range of throw	5 m.	7 m.
Average % Discharge	96%	97%
Operating Temperature	+5 °C to +55 °C	
Service Pressure (Ps)	15 bar.	
Max. Service Pressure (Pms)	17 bar.	
Test Pressure	35 bar.	
Expelling Agent	Nitrogen (UHP Grade)	
Full Weight (Approx.)	8 kg.	12 kg.
Empty Weight (Approx.)	2.9 kg.	4.3 kg.
Shipping Weight (Approx.)	8.2 kg.	12.3 kg.
Packing Standard	2 in 1- 22.5"X6.75"X14.10"	1 in 1- 24.75"X8"X8"
Mounting Bracket	Wall bracket	
Approvals	BIS & CE (on request)	

### Fire Rating as per IS 15683:2006

Type	MODEL	A	B
FOAM	KFM6-S	--	--
	KFM9-S	2A	21B

S

<b>Factory Tested A:B</b>
1A:21B
3A:34B