



## Product Short description for Enquiry HQ Series Kanex FE36 Clean Agent Fire Extinguishers

### CLEAN AGENT (FE 36) 2 KG SS BODY 1A:21B FIRE EXTINGUISHER

HQ	KCASS-2(FE36)	<b>KANEX 2 kg Clean Agent Fire Extinguisher filled with "DuPont "make UL listed &amp; FM Approved FE-36(HFC-236 fa) gas, Smooth and polished stainless steel body,</b> Electrically nonconductive non corrosive, colorless and non-residual gas, Applicable for Classes A, B, C, and electrical fires, <b>Approved with US EPA (environmental protection agency), listing under USA Signification New Alternative Policy ( SNAP), compliant with ASTM -D6541-11.</b> UGTS Pressure Gauge, Gross Weight 3.6 Kg, empty Weight 1.6 Kg, Height 440mm, Diameter 110 ± 10mm, Discharge Time 12 Sec, Controllable discharge mechanism, Jet Range 3 Meters, Average Discharge is 95%, <b>EPDM Rubber Hose with Special Aluminum Discharge Nozzle, CE Mark Valve with Safety Release Provision &amp; Safety pin is of SS material, Helium Leak Detection Tested, Fire rating 1A : 21B, FE36 having Zero Ozone Depletion Potential,</b> Confirms to IS 15683, <b>ISI &amp; CE marked,</b> Warrantee: 5 Years.
----	---------------	---

### CLEAN AGENT (FE 36) 4 KG SS BODY 1A:21B FIRE EXTINGUISHER

HQ	KCASS-4(FE36)	<b>KANEX 4 kg Clean Agent Fire Extinguisher filled with "DuPont "make UL listed &amp; FM Approved FE-36(HFC-236 fa) gas, Smooth and polished stainless steel body,</b> Electrically nonconductive non corrosive, colorless and non-residual gas, Applicable for Classes A, B, C, and electrical fires, <b>approved with US EPA (environmental protection agency), listing under USA Signification New Alternative Policy ( SNAP), compliant with ASTM -D6541-11.</b> UGTS Pressure Gauge, Gross Weight 6.3 Kg, empty Weight 2.3 Kg, Can Height 500mm, Diameter 140 ± 10mm, Discharge Time 14 Sec, Controllable discharge mechanism, Jet Range 3.5 Meters, Average Discharge is 95%, <b>EPDM Rubber Hose with Special Aluminum Discharge Nozzle, CE Mark Valve with Safety Release Provision &amp; Safety pin is of SS material, Helium Leak Detection Tested, Fire rating 1A : 21B, FE-36 having Zero Ozone Depletion Potential,</b> Confirms to IS 15683, <b>ISI &amp; CE marked,</b> Warrantee: 5 Years.
----	---------------	--