

Technical Details

MODEL	KCA-2(FE36)	KCA-4(FE36)	KCA-6(FE36)
Capacity	2 kg	4 kg	6 kg
Design	Hose & Nozzle		
Fire Rating	8B	1A : 13B	1A : 21B
Height (Approx.)	380 mm.	490 mm.	530 mm.
Diameter (Approx.)	106±10 mm.	140±10 mm.	150±10 mm.
Average Discharge time	12.5 Sec.	14 Sec.	22 Sec.
Average Range of throw	3 m.	3.5 m.	4 m.
Average % Discharge	96%	97%	96%
Operating Temperature	-20 °C to +55 °C	-20 °C to +55 °C	+5 °C to +55 °C
Service Pressure (Ps)	9 bar.		
Max. Service Pressure (Pms)	13 bar.		
Test Pressure	35 bar.		
Expelling Agent	Nitrogen (UHP Grade)		
Full Weight (Approx.)	3.6 kg.	6.7 kg.	8.9 kg.
Empty Weight (Approx.)	1.6 kg.	2.7 kg.	2.9 kg.
Shipping Weight (Approx.)	3.8 kg.	7.0 kg.	9.2 kg.
Packing Standard	Inner- 13.75"X4.75"X4.75" Outer (4 in 1)- 16.5"X10"X10"	2 in 1- 21"X6.75"X14.10"	2 in 1- 22.5"X6.75"X14.10"
Mounting Bracket	Vehicle/Wall bracket	Wall Barcket	
Approvals	BIS & CE		